SERIES	ONC
SHEET	J-26
EDITION	11

ONC J-26

ELEVATIONS IN FEET

ALL ELEVATION VALUES (AERONAUTICAL, RELIEF AND HYDROGRAPHIC) ARE BASED ON MEAN SEA LEVEL.

LEGEND

RELIEF PORTRAYAL

Elevations are in feet. HIGHEST TERRAIN elevation is:
7700 feet
located at **18°23'N 74°02'W**

TERRAIN CHARACTERISTIC TINTS



Green color indicates flat or relatively level terrain regardless of altitude above sea level.

CONTOURS

Basic interval 1000 feet.
Intermediate contours are shown only at 250 and 500 feet.

SPOT ELEVATIONS

Accurate elevations 0000
(Elevations are accurate to within 100 feet.)
Questionable elevations 0000
(Not to scale)
Location Undetermined 0000
(Vertical accuracy unknown)
Critical elevation 0000
Lake elevation 0000
Stream elevation 0000
Associated elevations (*) represent the latest vertical information and may not agree with contours.

CULTURE

Actual city outline ..... Towns and villages (Landmark feature unidentified) ..... Dirt trails
Primary roads ..... Secondary roads
Single-track R. R. ..... Multiple track R. R.
Individual tower ..... Power transmission line

LANDMARK FEATURE SYMBOLS

Castle ..... Monument
Church ..... Prominent
Factory ..... Ship pile
Lighthouse ..... Tower

ATTENTION
THIS CHART CONTAINS MAXIMUM ELEVATION FIGURES (MEF)

The Maximum Elevation Figures shown in quadrangles bound ed by ticked lines of latitude and longitude are represented in THOUSANDS and HUNDREDS of feet above mean sea level. The MEF is the highest elevation information available for the quadrangle and includes all cultural features such as towers, buildings, tankers and obstructions, (Trees, towers, antennas, etc.).

Example: 12,500 feet **12 5**

* In areas where elevation data contours appear in disagreement with the MEF, the MEF should be considered correct.

AERONAUTICAL INFORMATION

AERODROMES

Major ..... TACA 780
Major, runway pattern not available ..... PEDRO 10 (5282)

Major aerodromes portrayed have a hard surface runway length of 3000 feet or more. Runway patterns and a1000 foot diameter circle is drawn at 1:500,000 scale. When runway pattern is not shown, the number following the name indicates length of the longest runway to the nearest hundred feet.

Minor ..... BIMINI 190

VERTICAL OBSTRUCTIONS

Single 961 (1246)
Group/Multiple 961 (1246)
Highest vertical obstruction within 1 minute latitude and longitude 1474 (4686)

Radio facility obstruction 961 (1246)

1474 — Height of top above mean sea level (MSL)
(4686) — Height of top above ground level (AGL)

VERTICAL OBSTRUCTIONS SHOWN HAVE BEEN SELECTED FROM INFORMATION AVAILABLE AS OF MARCH 1999

All vertical obstructions 200 feet AGL and higher cannot be portrayed due to chart scale and feature density. In general, the highest obstruction in each 2 minute by 2 minute matrix (originating at full degree intersection) is shown, however, in areas of dense culture, this pattern is further reduced to enhance clarity.

CAUTION
Vertical Obstructions, including powerlines,have been extracted from the most reliable sources available; however, there is no assurance that all are shown or that their locations or heights are exact.

RADIO FACILITIES

- VHF OMNI RANGE (VOR)
- VORTAC
- TACAN
- VOR DME
- Other Facilities

SPECIAL USE AIRSPACE

LFR45

Alert, Danger, Prohibited, Restricted or Warning Areas. Numbers indicate internationally recognized numerical designators. Alert Areas are shown in light blue tint and or dashed in areas of overlap for clarity only.

All Special Use Airspace is portrayed in the body of this chart with the following exceptions:
(1) Those that are Alert Areas.
(2) Those that are intermittent.

NOTES

Depiction of international boundaries has been changed since the last edition.

The representation of boundaries is not necessarily authoritative.

No adequate source material was available to display vegetation patterns within the area of this chart.

WARNING AND OPERATING TIME DETERMINED BY DAYLIGHT SAVING TIME, DAYLIGHT SAVING TIME IS ADVANCED ONE HOUR FROM STANDARD TIME. TIME IS EXPRESSED IN HOURS AND HUNDREDTHS OF HOURS.

BLUE NUMBERED LINES INDICATE TRIGGER TIME IN METERS. YELLOW NUMBERED LINES INDICATE TRIGGER TIME IN FEET. (TRIGGER TIME IS 1 SECOND PER 1000 FEET)

SAMPLE AREA	TO REFERENCE TO SAMPLE POINT (NAUTICAL MILES)
	SAMPLE POINT (NAUTICAL MILES)
	1. Read below identifying TRIGGER TIME (Trigger Time is 1 second per 1000 feet)
	2. Locate the WARNING point on a side by side chart and determine (MILES) from column
	3. Determine tactics from grid line to point (Tactics are based on a speed of 600 knots)
	4. Locate the WARNING point on the chart and determine (MILES)
	5. Determine tactics from grid line to point
	A. Depicting Natural PTS (i.e. WP) ON points, the Grid Line Designation, etc.
	B. Depicting Artificial PTS (i.e. WP) ON points, the Grid Line Designation, etc.

COMPUTER GRID VALUES ARE SHOWN TO EXTREMES FOR COORDINATES, REMAINING VALUES IN NUMBER AREA REFLECT DIVISIONS OF LAST FOUR DIGITS.

Entire Primary UTM Grid falls within World Geodetic System 1980 Ellipsoid

Entire Secondary UTM Grid falls within Clarke 1866 Ellipsoid

THE NORTH AMERICAN DATUM 1983 (NAD83) AND THE WORLD GEODETIC REFERENCE SYSTEM 1984 (WGS84) ARE FUNDAMENTALLY EQUIVALENT FOR MAPPING, CHARTING AND NAVIGATION AT OUR SCALES.

Civil users may purchase NIMA products by ordering them from the following address:
NOAA Distribution Branch (N/ACC2)
National Ocean Service
Riverdale, MD. 20737-1199

ONC J-26

BAHAMAS, CAYMAN ISLANDS, CUBA, HAITI, JAMAICA, NAVASSA ISLAND

SCALE 1:1,000,000

Prepared and published by the National Imagery and Mapping Agency. Compiled February 1969. Revised July 1997. (Revision limited to aeronautical information, correction of all CRUM conditions, and currency of planimetric detail.)

COPYRIGHT 1998 BY THE UNITED STATES GOVERNMENT
NO COPYRIGHT CLAIMED UNDER TITLE 17 USC.

Reprinted by NIMA 8-02

SERIES	ONC
SHEET	J-26
EDITION	11

Lambert Conformal Conic Projection
Standard Parallels 17°20' and 27°40'
Convergence Factor: .34213

CAUTION
AIR INFORMATION CURRENT THROUGH
26 MARCH 1999
Before using this chart, consult the current NIMA Aeronautical Chart Updating Manual (CHUM/CHART), Aeronautical Flight Information File (AFIF), Notices To Airmen Publications (FLIP) and Notices to Airmen (NOTAMS) for vital updating information.

LINES OF EQUAL MAGNETIC VARIATION FOR 1995 (Annual Rate of Change -9' increase)

NSN 7641014099605
ED. NO. 011
NIMA PRT. NO. ONCXXJ.J26

INTERCHART RELATIONSHIP
The representation of boundaries is not necessarily authoritative.



ONC chart identification J-26
World Area Code identifies 585
World Area Code identifiers are also carried in the body of this chart by corner ticks and numbers.

ELEVATIONS IN FEET

NAUTICAL MILES 0 10 20 30 40 50 60 70 80 90 100 110 120
STATUTE MILES 0 10 20 30 40 50 60 70 80 90 100 110 120 130 140 150
KILOMETERS 0 20 40 60 80 100 120 140 160 180 200 220 240 260 280

CONVERSION OF ELEVATIONS

FEET (Thousands)	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
METERS (Thousands)	1	1	2	2	3	3	4	4	5	5	6	6	7	7	8	8	9	9	10	10

OPERATIONAL NAVIGATION CHART
1:1,000,000

ELEVATIONS IN FEET

GLOSSARY

Archipiélago	islands
Bahía	bay
Cabo	cape
Cabo	cape
Canal	marine channel
Cay	island
Cay	island
Cayo	island
Cayo	islands
Cayos	islands
Cénagas	marsh(es)
Embalse	reservoir(s)
Golfo	gulf
Isla	island
Isla	island
Islas	islands
Isleta	islands
Monte	mountain
Península	peninsula
Pico	mountain
Punta	point
Presa	reservoir(s)
Río	stream
Río	stream
Sierra	mountains

USERS SHOULD REFER CORRECTIONS, ADDITIONS, AND COMMENTS TO THE NIMA OPERATIONAL HELP DESK: 1-800-455-0884 (COMMERCIAL) OR 202-4854-2390-DSN 4854 OR WRITE TO: DIRECTOR, NATIONAL IMAGERY AND MAPPING AGENCY, ATTN: ES, MAIL STOP L-40, 4600 SANGAMORE ROAD, BETHESDA, MD 20816-5003.

WORLD GEOGRAPHIC REFERENCE SYSTEM (RED BROWN)

SAMPLE AREA — REFERENCE TO WITHIN ONE MINUTE

SAMPLE POINT - MARICOUBA

1. Read GREENIP values from left to right and bottom to top.
2. Read below identifying letter (or2 letters) in which the point lies.
3. Locate the point lying 9 quadrangle in which the point lies.
4. Locate the four MINUTE lat of LONGITUDE values and determine GREENIP values.
5. Locate the MINUTE lat of LATITUDE values and determine GREENIP value.

SAMPLE REFERENCE

ONC J-26

SERIES	ONC
SHEET	J-26
EDITION	11