

Department of Computer Science Technical Report

Counterexamples in Probabilistic Model Checking

Tingting Han and Joost-Pieter Katoen

ISSN 0935–3232 · Aachener Informatik Berichte · AIB-2006-09 RWTH Aachen · Department of Computer Science · August 2006

The publications of the Department of Computer Science of RWTH Aachen University are in general accessible through the World Wide Web.

http://aib.informatik.rwth-aachen.de/

Counterexamples in Probabilistic Model Checking

Tingting Han and Joost-Pieter katoen

Lehrstuhl für Informatik 2 RWTH Aachen, Germany Email: {tingting.han, katoen}@informatik.rwth-aachen.de

Abstract. This paper considers algorithms and complexity results for the generation of counterexamples in model checking of probabilistic until-formulae in discrete-time Markov chains (DTMCs). It is shown that finding the strongest evidence (i.e, the most probable path) that violates a (bounded) until-formula can be found in polynomial time using single-source (hop-constrained) shortest path algorithms. We also show that computing the smallest counterexample that is mostly deviating from the required probability bound can be found in a pseudopolynomial time complexity by adopting a certain class of algorithms for the (hop-constrained) k shortest paths problem.

1 Introduction

A major strength of model checking is the possibility to generate counterexamples in case a property is violated. The shape of a counterexample depends on the temporal logic used. For LTL and the universal fragment of CTL, a single path through the system model suffices to indicate the refutation of the property. For existentially quantified path-formulae in logics such as CTL, either witnesses are provided (to indicate why the property holds), or more advanced structures such as trees of paths [10] or annotated paths [28] are provided as counterexample. Counterexamples are of utmost importance in model checking: they provide diagnostic feedback (also in cases where only a fragment of the entire model can be searched), they constitute the key to successful abstraction-refinement techniques [9], and are at the core of obtaining (optimal) schedules in e.g. timed model checking [7]. As a result, advanced counterexample generation and analysis techniques have intensively been investigated, see e.g., [23, 6, 12].

In probabilistic model checking, however, counterexample generation is almost not developed [2, 3]. Probabilistic model checking is a technique to verify system models in which transitions are equipped with randomness. Popular models are discrete- and continuous-time Markov chains (DTMCs and CTMCs), and variants thereof which exhibit nondeterminism. Efficient model-checking algorithms have been developed for these models, and have been applied to case studies from various application areas. The crux of probabilistic model checking is to combine techniques from numerical mathematics with standard reachability analysis. In this way, properties such as "the probability to reach a set of goal states is at most 0.6" can be automatically checked (up to a certain precision).

In the probabilistic setting, typically there is no single trace (but rather a set of them) that indicates why a given property is refuted. In case of a property refutation, current probabilistic model checkers produce a log file that shows the computed probability for all states. This information is too detailed to aid as a useful support in finding the cause(s). This paper considers algorithms and complexity results for the generation of counterexamples in model checking of (a safe fragment of) probabilistic CTL [20] on DTMCs. We concentrate on properties of the form $\mathcal{P}_{\leqslant p}(\Phi \mathcal{U}^{\leqslant h}\Psi)$. In case *s* refutes this formula, the probability of all paths in *s* satisfying $\Phi \mathcal{U}^{\leqslant h}\Psi$ exceeds *p*. We first consider the generation of *strongest evidences* for violation, i.e., paths satisfying $\Phi \mathcal{U}^{\leqslant h}\Psi$ that have the largest probability mass. Strongest evidences "contribute" mostly to the property refutation. For unbounded until (i.e., $h=\infty$), determining strongest evidences is equivalent to a standard shortest path (SP) problem; in case *h* is bounded, we obtain a special case of the (resource) constrained shortest path (CSP) problem [1] that can be solved in $\mathcal{O}(hm)$ where *m* is the number of transitions in the DTMC.

As most probable paths may have a very small probability mass, their information may be limited. As a next step, therefore, we consider the problem of determining most probable subtrees. Whereas in traditional model checking one is interested in the shortest counterexample, we consider trees of *smallest size* that exceed the probability bound *maximally*. The problem of generating such smallest, most indicative counterexamples can be casted as a k shortest paths problem. For unbounded-until formulae (i.e., $h=\infty$), it is shown that the generation of such smallest counterexamples can be found in pseudo-polynomial time by adopting k shortest path algorithms [14, 17, 26] that can compute k on the fly. For bounded until-formulae, we propose a variant of the recursive enumeration algorithm of Jiménez and Marzal [22]. The time complexity of this adapted algorithm is $\mathcal{O}(hm+hk\log(\frac{m}{n}))$, where n is the number of states in the DTMC.

2 Preliminaries

This section introduces DTMCs and the logic PCTL-safety.

2.1 DTMCs

Definition 1 (DTMCs). A (labelled) discrete-time Markov chain (DTMC) is a tuple $\mathcal{D} = (S, \mathbf{P}, L)$ where:

- -S is a finite set of states;
- $\mathbf{P}: S \times S \rightarrow [0,1]$ is a probability matrix satisfying $\sum_{s' \in S} \mathbf{P}(s,s') = 1$ for all $s \in S$;
- $-L: S \to 2^{AP}$ is a labelling function which assigns to each state $s \in S$ the set L(s) of atomic propositions that are valid in s.

A state s in \mathcal{D} is called absorbing if $\mathbf{P}(s, s) = 1$. W.l.o.g. we assume a DTMC to have a unique initial state.

Definition 2 (Paths). Let $\mathcal{D} = (S, \mathbf{P}, L)$ be a DTMC.

- An infinite path σ in \mathcal{D} is an infinite sequence $s_0 \cdot s_1 \cdot s_2 \cdot \ldots$ of states such that $\mathbf{P}(s_i, s_{i+1}) > 0$ for all $i \ge 0$.
- -A finite path in \mathcal{D} is a finite prefix of an infinite path.

For state s and path σ , $\sigma \cdot s$ denotes the path obtained by extending σ by s. Let $|\sigma|$ denote the length of the path σ , i.e., $|s_0 \cdot s_1 \cdot \ldots \cdot s_n| = n$, $|s_0| = 0$ and $|\sigma| = \infty$ for

infinite σ . For $0 \leq i \leq |\sigma|$, $\sigma[i] = s_i$ denotes the *i*-th state in σ . Path(s) denotes the set of infinite paths that start in state s, formally, $Path(s) = \{\sigma \mid \sigma[0] = s\}$. Let $Path_{fin}(s)$ denotes the set of finite paths that start in state s.

A DTMC \mathcal{D} enriched with an initial state s_0 induces a probability space. The underlying σ -algebra from the basic cylinders is induced by the finite paths starting in s_0 . The probability measure $\Pr_{s_0}^{\mathcal{D}}$ (briefly Pr) induced by (\mathcal{D}, s_0) is the unique measure on this σ -algebra where:

$$\Pr\{\underbrace{\sigma \in Path(s_0) \mid s_0 \cdot s_1 \cdot \dots \cdot s_n \text{ is a prefix of } \sigma}_{\text{basic cylinder of the finite path } s_0 \cdot s_1 \cdot \dots \cdot s_n} = \prod_{0 \leq i < n} \mathbf{P}(s_i, s_{i+1}).$$

Example 1. Fig. 1 illustrates a simple DTMC consisting of 10 states. s is the initial state, $AP = \{a, b\}$ and L is given through the subsets of AP labelling the states as $L(s) = L(s_i) = \{a\}$, for $1 \leq i \leq 4$; $L(t_1) = L(t_2) = L(t_3) = \{b\}$ and $L(u_1) = L(u_2) = \emptyset$. The DTMC contains no absorbing states. $\sigma_1 = s \cdot u_1 \cdot u_2 \cdot s_1 \cdot t_1 \cdot s_3$ is a finite path in this DTMC with $\Pr\{\sigma_1\} = 0.1 \times 0.4 \times 0.8 \times 0.1 \times 1 = 0.0032$ and $|\sigma_1| = 5$, $\sigma_1[3] = s_1$. $\sigma_2 = s \cdot s_3 \cdot (s_4 \cdot t_3)^{\omega}$ is an infinite path, $|\sigma_2| = \infty$.



Fig. 1. An example DTMC

2.2 PCTL-safety

In this paper, counterexamples are explored when properties specified in the safety fragment of PCTL [5] are violated. The syntax and semantics of PCTL-safety are given and its expressiveness is illustrated by some examples.

Syntax. Let $p \in [0, 1]$ and let AP denote a fixed, finite set of atomic propositions ranged over by a, b, c, \ldots . The syntax of PCTL-safety state formulae (in positive normal form, i.e., negations can only occur adjacent to atomic propositions.) is defined as follows:

$$\Phi ::= \operatorname{tt} \mid \operatorname{ff} \mid a \mid \neg a \mid \Phi \land \Phi \mid \Phi \lor \Phi \mid \mathcal{P}_{\leq p}(\phi)$$

where ϕ is path-formula defined by

$$\phi ::= \Phi \mathcal{U}^{\leqslant h} \Phi,$$

where $h \in \mathbb{N} \cup \{\infty\}$. We call the operator $\mathcal{U}^{\leq h}$ unbounded until if $h = \infty$ and abbreviate it as \mathcal{U} ; and call it bounded until otherwise. For the sake of simplicity, we do not consider the next-operator. Note that the main distinction with PCTL [20] is that the probability bounds are upper bounds, and formulae are required to be in positive normal form.

As for CTL, the temporal operator $\diamondsuit^{\leq h}$ (eventually) can be derived as

$$\mathcal{P}_{\leqslant p}(\diamondsuit^{\leqslant h}\Phi) = \mathcal{P}_{\leqslant p}(\mathrm{tt}\ \mathcal{U}^{\leqslant h}\ \Phi)$$

The dual form is defined as $\mathcal{P}_{>p}(\Box^{\leqslant h}\Phi) = \mathcal{P}_{\leqslant 1-p}(\diamondsuit^{\leqslant h}\neg\Phi)$. Note that the negation can be "pushed" inside Φ until finally it is adjacent to an atomic proposition (see [5])¹. For the more general case, $\mathcal{P}_{>p}(\Phi \mathcal{W}^{\leqslant h}\Psi) = \mathcal{P}_{\leqslant 1-p}(\neg \Psi \mathcal{U}^{\leqslant h}\neg(\Phi \lor \Psi))$. Thus in the PCTL-safety fragment, four forms $\mathcal{P}_{\leqslant p}(\Phi \mathcal{U}^{\leqslant h}\Psi)$, $\mathcal{P}_{>p}(\Phi \mathcal{W}^{\leqslant h}\Psi)$, $\mathcal{P}_{\leqslant p}(\Phi \mathcal{W}^{\leqslant h}\Psi)$, $\mathcal{P}_{>p}(\Phi \mathcal{W}^{\leqslant h}\Psi)$, $\mathcal{P}_{\leqslant p}(\Phi \mathcal{W}^{\leqslant h}\Phi)$ and $\mathcal{P}_{>p}(\Box^{\leqslant h}\Phi)$ are allowed.

Semantics. Let DTMC $\mathcal{D} = (S, \mathbf{P}, L)$. The semantics of PCTL-safety is defined by a satisfaction relation, denoted \models , which is characterized as the least relation over the states in S (infinite paths in \mathcal{D} , respectively) and the state formulae (path formulae). The semantics of the propositional fragment is identical to that for CTL. The meaning of the probabilistic operator is formalized as follows [20]. The semantics of PCTL-safety state formulae is defined for path formula ϕ as:

Let $Path(s, \phi)$ denote the set of infinite paths that start in state s and satisfy ϕ . Formally, $Path(s, \phi) = \{\sigma \in Path(s) \mid \sigma \models \phi\}$. Here, $Prob(s, \phi) = \Pr\{\sigma \in Path(s, \phi)\}$ denotes the probability of $Path(s, \phi)$. Let σ be an infinite path in \mathcal{D} . The semantics of PCTL-safety path formulae is defined as:

 $\sigma \models \Phi \mathcal{U}^{\leqslant h} \Psi \quad \text{iff} \quad \exists i \leqslant h \text{ such that } \sigma[i] \models \Psi \text{ and } \forall j : 0 \leqslant j < i.(\sigma[j] \models \Phi).$

For finite path σ , \models is defined in a similar way by changing the range of *i* to $i \leq \max\{h, |\sigma|\}$. Let $Path_{fin}(s, \phi)$ denote the set of finite paths starting in *s* that fulfill ϕ .

Example 2. We give some examples to illustrate how the PCTL-safety formulae are utilized to specify system properties.

- In Fig. 1, $\mathcal{P}_{\leq 0.27}(a\mathcal{U}b)$ asserts that the probability of reaching a *b*-state via an *a*-path is at most 0.27.

¹ During the transformation, arbitrary PCTL-formulae can occur, but the result is again a PCTL-safety formula.

- Let *error* be an atomic proposition that characterizes any state in which a system error has occurred. Then $\mathcal{P}_{\leq 0.001}(\diamondsuit^{\leq 50} error)$ asserts that the probability for a system error to occur within 50 steps is at most 0.001. Dually, $\mathcal{P}_{>0.999}(\Box^{\leq 50}\neg error)$ states that the probability for not having a system error (running successfully) within 50 steps exceeds 0.999.
- Let *red* and *green* be two atomic propositions. $\mathcal{P}_{>0.8}(\text{green } W \text{ red})$ asserts that the probability of either being green forever, or reaching a red state via a green path, is greater than 0.8. Stated differently, with probability at most 0.2, a state is reached that is neither red nor green via a path that does not contain a red state, which can be specified by the dual formula $\mathcal{P}_{\leq 0.2}((\neg \text{red})\mathcal{U}(\neg \text{green} \land \neg \text{red})).$

3 Counterexamples in a probabilistic setting

Let us first consider what a counterexample actually is. To that end, consider the formula $\mathcal{P}_{\leq p}(\phi)$, where ϕ is a path-formula. If state s refutes $\mathcal{P}_{\leq p}(\phi)$:

$$\begin{split} s \nvDash \mathcal{P}_{\leqslant p}(\phi) \\ \text{iff} & \text{not} \ (Prob(s,\phi)\leqslant p) \\ \text{iff} & Prob(s,\phi) > p \\ \text{iff} & \Pr\{\sigma \mid \sigma \in Path(s,\phi)\} > p \end{split}$$

So, $\mathcal{P}_{\leq p}(\phi)$ is refuted by state *s* whenever the total probability mass of all ϕ -paths that start in *s* exceeds *p*. This indicates that a counterexample for $\mathcal{P}_{\leq p}(\phi)$ is in general a *set* of paths satisfying ϕ . As ϕ is an until-formula and can be witnessed by finite state sequences, finite paths do suffice in counterexamples. As a counterexample should exceed *p*, a maximally probable ϕ -path is a strong evidence for the violation of $\mathcal{P}_{\leq p}(\phi)$. For counterexamples that are as small as possible, i.e., that contain the smallest possible set of paths indicating the refutation, such maximally probable paths are essential.

Definition 3 (Strongest evidence). A strongest evidence for violating $\mathcal{P}_{\leq p}(\phi)$ in state s is a finite path $\sigma \in Path_{fin}(s, \phi)$ such that $Pr\{\sigma\} \geq Pr\{\sigma'\}$ for any $\sigma' \in Path_{fin}(s, \phi)$.

Dually, a strongest evidence for violating $\mathcal{P}_{\leq p}(\phi)$ is a strongest witness for $\mathcal{P}_{>p}(\phi)^2$. Note that a strongest evidence does not need to be a counterexample as its probability mass may be (far) below p. A counterexample is defined as follows:

Definition 4 (Counterexample). A counterexample for $\mathcal{P}_{\leq p}(\phi)$ in state *s* is a set *C* of paths such that $C \subseteq Path_{fin}(s, \phi)$ and Pr(C) > p.

Note that counterexamples are always finite as we consider non-strict upperbounds in the probability operator³. Let $CX_p(s, \phi)$ be the set of counterexamples for $\mathcal{P}_{\leq p}(\phi)$ in state s. For $C \in CX_p(s, \phi)$ and C's superset C': $C \subseteq C' \subseteq$

 $^{^{2}\}mathcal{P}_{>p}(\phi)$ is a PCTL-formula, not necessarily a safe one.

³ For strict upper bounds in the probability operator, i.e., $\mathcal{P}_{< p}(\phi)$, a counterexample *C* may contain infinite paths, since $\Pr(C) = p$ is a counterexample. The limit of the sum of path probabilities obeying a geometric distribution may equal p, but the limit requires infinite paths.

 $Path_{fin}(s, \phi)$, it follows that $C' \in CX_p(s, \phi)$, since $Pr(C') \ge Pr(C) > p$. A counterexample is called *minimal* if it is minimal w.r.t. \subseteq . Note that a counterexample for state s is a set of finite paths that all start in s, and thus can be considered as a finite tree rooted at s.

As in conventional model checking, we are not interested in generating arbitrary counterexamples, but those that are easy to comprehend, and provide a clear evidence of the refutation of the formula. So, akin to shortest counterexamples we define the notion of a smallest, most indicative counterexample. Such smallest counterexamples should contain as few paths as possible—allowing easier analysis of the cause of refutation—but whose probability is clearly exceeding p.

Definition 5 (Smallest counterexample). $C \in CX_p(s, \phi)$ is a smallest (most indicative) counterexample *if:*

1. $|C| \leq |C'|$, for any $C' \in CX_p(s, \phi)$ and 2. $Pr(C) \geq Pr(C'')$, for any $C'' \in CX_p(s, \phi)$ and |C| = |C''|.

Intuitively, a smallest counterexample is mostly deviating from the required probability bound given that it has the smallest number of paths. Any smallest counterexample is minimal, but not necessarily the reverse. Note that the strongest evidence, minimal counterexample or smallest counterexample may not be unique, as paths may have equal probability. As a result, not every strongest evidence is contained in a minimal (or smallest) counterexample. However, any smallest counterexample contains at least one strongest evidence.

Example 3. In the DTMC in Fig. 1, we have $s \not\models \mathcal{P}_{\leq 0.27}(a\mathcal{U}b)$. Let $\sigma_1 = s \cdot s_1 \cdot s_2 \cdot t_2$, $\sigma_2 = s \cdot s_1 \cdot s_3 \cdot s_4 \cdot t_1$, $\sigma_3 = s \cdot s_1 \cdot s_3 \cdot s_4 \cdot t_2$, $\sigma_4 = s \cdot s_3 \cdot s_4 \cdot t_1$, $\sigma_5 = s \cdot s_3 \cdot s_4 \cdot t_2$, $\sigma_6 = s \cdot s_3 \cdot s_4 \cdot t_3$, where:

$$\Pr\{\sigma_1\} = 0.12, \ \Pr\{\sigma_2\} = \Pr\{\sigma_3\} = \Pr\{\sigma_4\} = \Pr\{\sigma_5\} = 0.072, \ \Pr\{\sigma_6\} = 0.018.$$

Path σ_1 is a strongest evidence, as it is the maximally probable path from s to $\{t_1, t_2, t_3\}$, i.e., b-states. The set $C_1 = \{\sigma_2, \sigma_3, \sigma_4, \sigma_5, \sigma_6\}$ with $\Pr(C_1) = 0.306$ is a counterexample, but neither a minimal counterexample, nor a smallest counterexample, as $C_2 = \{\sigma_2, \sigma_3, \sigma_4, \sigma_5\} \subset C_1$ with $\Pr(C_2) = 0.288$ is also a counterexample. C_2 is a minimal counterexample, since the probability of any proper subset of C_2 is less than 0.27. But C_2 is not a smallest counterexample, as $C_3 = \{\sigma_1, \sigma_2, \sigma_3, \sigma_4\}$ with $\Pr(C_3) = 0.336$ is a counterexample too and $|C_2| = |C_3|$ but $\Pr(C_3) > \Pr(C_2)$. In fact, any set containing the strongest evidence and any three paths in C_2 is a smallest counterexample.

In the remainder of the paper, we first consider the computation of strongest evidences. Formally, we consider the strongest evidence problem (SE), that for a given state s with $s \not\models \mathcal{P}_{\leq p}(\phi)$, determines the strongest evidence for this violation. Subsequently, we consider the corresponding smallest counterexample problem (SC). For both cases, we distinguish between until-formulae for which $h=\infty$ (unbounded until) and $h \in \mathbb{N}$ (bounded until) as distinctive algorithms are used for these cases.

4 From DTMC to a weighted digraph

Prior to finding strongest evidences or shortest counterexamples, we first modify the DTMC and turn it into a weighted directed graph. Let $\phi = \Phi \mathcal{U}^{\leq h} \Psi$, $h = \infty$ or $h \in \mathbb{N}$ and $Sat(\Phi) = \{s \in S \mid s \models \Phi\}$ for any state-formula Φ . Due to the bottom-up traversal of the model-checking algorithm over the formula ϕ , we may assume that $Sat(\Phi)$ and $Sat(\Psi)$ are known.

Step 1: Adapting the DTMC. First, we make all states in the DTMC $\mathcal{D} = (S, \mathbf{P}, L)$ that neither satisfy Φ nor Ψ absorbing. Then we add an extra state t so that all the Ψ -states are equipped with a transition to t with probability 1 (all other outgoing transitions of Ψ -states are omitted). State t can thus only be reached via a Ψ -state. The thus obtained DTMC $\mathcal{D}' = (S', \mathbf{P}', L')$ has state space $S \cup \{t\}$ for $t \notin S$. The transition probabilities in \mathcal{D}' are defined as follows:

$$\begin{cases} \mathbf{P}'(s',s') = 1 \text{ and } \mathbf{P}'(s',s'') = 0 \text{ for } s'' \neq s' & \text{if } s' \notin \operatorname{Sat}(\Phi) \cup \operatorname{Sat}(\Psi) \text{ or } s' = t \\ \mathbf{P}'(s',t) = 1 \text{ and } \mathbf{P}'(s',s'') = 0 \text{ for } s'' \neq t & \text{if } s' \in \operatorname{Sat}(\Psi) \\ \mathbf{P}'(s',s'') = \mathbf{P}(s',s'') \text{ for } s'' \in S \text{ and } \mathbf{P}'(s',t) = 0 & \text{otherwise} \end{cases}$$

L'(s') = L(s') for $s' \in S$ and $L'(t) = \{at_t\}$, where $at_t \notin L(s')$ for any $s' \in S$, i.e., at_t uniquely identifies being at state t. Remark that all the $(\neg \Phi \land \neg \Psi)$ -states could be collapsed into a single state, but this is not further explored here. The time complexity of this transformation is $\mathcal{O}(n)$ where n = |S|.

It is evident that the validity of $\mathcal{P}\mathcal{U}^{\leq h}\Psi$ is not affected by this amendment of the DTMC. All paths in \mathcal{D}' of length at most h + 1 that end in t satisfy $\mathcal{P}\mathcal{U}^{\leq h}\Psi$ in \mathcal{D} . More precisely, any finite path satisfying $(\mathcal{P} \vee \Psi)\mathcal{U}^{\leq h+1}at_t$ in \mathcal{D}' has a finite path in \mathcal{D} satisfying $\mathcal{P}\mathcal{U}^{\leq h}\Psi$. The following lemma guarantees that the later results in \mathcal{D}' also hold in \mathcal{D} .

Lemma 1. Let $\sigma' = \sigma \cdot t$ be a path in $Path_{fin}(s)$ in \mathcal{D}' . Then:

1. $\sigma' \models (\Phi \lor \Psi) \mathcal{U}^{\leqslant h+1} at_t \text{ in DTMC } \mathcal{D}';$ 2. $\sigma \models \Phi \mathcal{U}^{\leqslant h} \Psi \text{ in DTMC } \mathcal{D};$ 3. $\Pr\{\sigma\} = \Pr\{\sigma'\}.$

For the rest of the technical report, we suppose that all the DTMCs are the results of Step 1, and the logic formula considered is $(\Phi \lor \Psi)\mathcal{U}^{\leq h+1}at_t$.

Step 2: Conversion into a weighted digraph. As a second preprocessing step, the DTMC obtained in the first phase is transformed into a weighted digraph. Recall that a weighted digraph is a tuple $\mathcal{G} = (V, E, w)$ where V is a finite set of vertices, $E: V \times V$ is a set of edges, and $w: E \to \mathbb{R}_{\geq 0} \cup \{\infty\}$ is a function assigning non-negative weights to edges.

Definition 6 (Weighted digraph of a DTMC). For $DTMC \mathcal{D} = (S, \mathbf{P}, L)$, the weighted digraph $\mathcal{G}_D = (V, E, w)$ where:

$$- V = S \text{ and } (v, v') \in E \text{ iff } \mathbf{P}(v, v') > 0, \text{ and} \\ - w(v, v') = \begin{cases} \log(\mathbf{P}(v, v')^{-1}) & \text{if } \mathbf{P}(v, v') > 0, \\ \infty & \text{otherwise.} \end{cases}$$

Note that in any DTMC, $\mathbf{P}(s, s') \in [0, 1]$, thus $\mathbf{P}(s, s')^{-1} \in [1, +\infty)$, and consequently, $\log(\mathbf{P}(s, s')^{-1}) \in [0, +\infty)$. Thus, we indeed obtain a non-negatively weighted digraph. Note that this transformation can be done in $\mathcal{O}(m)$, where $m = |\mathbf{P}|$.

Example 4. The transformation from DTMC in Fig. 1 to a weighted digraph is illustrated in Fig. 2. For the path formula $\phi = a\mathcal{U}b$, in Fig. 2(a) all the *b*-states (i.e., t_1, t_2, t_3) are made absorbing and take a transition with probability 1 into the new state *t* (indicated by a double circle). All the $(\neg a \land \neg b)$ -states (i.e., u_1, u_2) are made absorbing and then (to simplify the figure) collapsed into one state *u*. In Fig. 2(b), the resulting weighted digraph is depicted where all the states remain the same, however the edge weights are obtained by taking the logarithm of the reciprocal of the corresponding transition probabilities.



Fig. 2. Transformation from DTMC to weighted digraph

A path σ from s to t in \mathcal{G} is a sequence $\sigma = v_0 \cdot v_1 \cdot \ldots \cdot v_j \in V^+$, where $v_0 = s, v_j = t$ and $(v_i, v_{i+1}) \in E$, for $0 \leq i < |\sigma|$. As for paths in DTMCs, $|\sigma|$ denotes the length of σ . The distance of finite path $\sigma = v_0 \cdot v_1 \cdot \ldots \cdot v_j$ in graph \mathcal{G} is $d(\sigma) = \sum_{i=0}^{j-1} w(v_i, v_{i+1})$. Due to the fact that multiplication of probabilities in \mathcal{D} corresponds to addition of weights in \mathcal{G}_D , and that weights are based on taking

the logarithm of the reciprocal of the transition probabilities in \mathcal{D} , distances in \mathcal{G} and path-probabilities in DTMC \mathcal{D} are related as follows.

Lemma 2. Let σ and σ' be finite paths in DTMC \mathcal{D} and its graph \mathcal{G}_D . Then:

$$\Pr\{\sigma'\} \ge \Pr\{\sigma\} \quad iff \quad d(\sigma') \le d(\sigma).$$

Proof. Consider the following finite path σ in \mathcal{D} :

$$\sigma = s_0 \xrightarrow{\mathbf{P}(s_0, s_1)} s_1 \xrightarrow{\mathbf{P}(s_1, s_2)} s_2 \cdots s_{n-1} \xrightarrow{\mathbf{P}(s_{n-1}, s_n)} s_n$$

By definition, its probability is:

$$\Pr\{\sigma\} = \mathbf{P}(s_0, s_1) \cdot \mathbf{P}(s_1, s_2) \cdots \mathbf{P}(s_{n-1}, s_n) = \prod_{i=0}^{n-1} \mathbf{P}(s_i, s_{i+1})$$

Consider an alternative path σ' :

$$\sigma' = s'_0 \xrightarrow{\mathbf{P}(s_0, s'_1)} s'_1 \xrightarrow{\mathbf{P}(s'_1, s'_2)} s'_2 \cdots s'_{m-1} \xrightarrow{\mathbf{P}(s'_{m-1}, s'_m)} s'_m$$
$$\Pr\{\sigma'\} = \mathbf{P}(s'_0, s'_1) \cdot \mathbf{P}(s'_1, s'_2) \cdots \mathbf{P}(s'_{m-1}, s'_m) = \prod_{i=0}^{m-1} \mathbf{P}(s'_i, s'_{i+1})$$

If $\Pr\{\sigma'\} \ge \Pr\{\sigma\}$, we have:

$$\begin{split} &\prod_{i=0}^{m-1} \mathbf{P}(s'_{i}, s'_{i+1}) \geqslant \prod_{i=0}^{n-1} \mathbf{P}(s_{i}, s_{i+1}) \\ \Leftrightarrow & \frac{1}{\prod_{i=0}^{m-1} \mathbf{P}(s'_{i}, s'_{i+1})} \leqslant \frac{1}{\prod_{i=0}^{n-1} \mathbf{P}(s_{i}, s_{i+1})} \\ \Leftrightarrow & \log(\frac{1}{\prod_{i=0}^{m-1} \mathbf{P}(s'_{i}, s'_{i+1})}) \leqslant \log(\frac{1}{\prod_{i=0}^{n-1} \mathbf{P}(s_{i}, s_{i+1})}) \\ \Leftrightarrow & \sum_{i=0}^{m-1} \log(\frac{1}{\mathbf{P}(s'_{i}, s'_{i+1})}) \leqslant \sum_{i=0}^{n-1} \log(\frac{1}{\mathbf{P}(s_{i}, s_{i+1})}) \\ \Leftrightarrow & \sum_{i=0}^{m-1} w(s'_{i}, s'_{i+1}) \leqslant \sum_{i=0}^{n-1} w(s_{i}, s_{i+1}) \\ \Leftrightarrow & d(\sigma^{*}) \leqslant d(\sigma) \end{split}$$

Note that Lemma 2 also holds for infinite paths. The following lemma specifies the correspondence between paths in DTMC D and its weighted digraph.

Lemma 3. For any path σ from s to t in DTMC \mathcal{D} and k > 0:

- 1. σ is a k-th most probable path in \mathcal{D} iff σ is a k-th shortest path in \mathcal{G}_D ;
- 2. σ is a k-th most probable path of at most h hops in \mathcal{D} iff σ is a k-th shortest path of at most h hops in \mathcal{G}_D ;

The correspondence between path probabilities in the DTMC and distances in its weighted digraph constitutes the basis for the remaining algorithms.

5 Finding strongest evidences

This section considers algorithms for determining strongest evidences, i.e., maximally probable paths.

5.1 Unbounded until

Based on the results of Lemma 3.1 where k = 1, we consider the shortest path problem.

Definition 7 (SP problem). Given a weighted digraph $\mathcal{G} = (V, E, w)$ and $s, t \in V$, the shortest path (SP) problem is to determine a path σ from s to t such that $d(\sigma) \leq d(\sigma')$ for any path σ' from s to t in \mathcal{G} .

From Lemma 3.1 together with the transformation of a DTMC into a weighted digraph, it follows that there is a polynomial reduction from the SE problem for unbounded until to the SP problem. As the SP problem is known to be in PTIME, it follows:

Theorem 1. The SE problem for unbounded until is in PTIME.

Various efficient algorithms [13, 8, 15, 11] exist for the SP problem, e.g., when using Dijkstra's algorithm, the SE problem for unbounded until can be solved in time $\mathcal{O}(m + n \log n)$ when using appropriate data structures such as Fibonacci heaps.

5.2 Bounded until

Lemma 3.2 when k = 1 applies when considering maximally probable paths of a certain maximal hop count. This suggests to consider the hop-constrained shortest path problem.

Definition 8 (HSP problem). Given a weighted digraph $\mathcal{G} = (V, E, w)$, $s, t \in V$ and $h \in \mathbb{N}$, the hop-constrained SP (HSP) problem is to determine a path σ in \mathcal{G} from s to t with $|\sigma| \leq h$ such that $d(\sigma) \leq d(\sigma')$ for any path σ' from s to t with $|\sigma'| \leq h$.

The HSP problem is a special case of the constrained shortest path (CSP) problem [27, 1], where the only constraint is the hop count.

Definition 9 (CSP problem). Given a weighted digraph $\mathcal{G} = (V, E, w), s, t \in V$ and resource constraints λ^i , for $1 \leq i \leq c$. Edge $e \in E$ uses $r^i(e) \geq 0$ units of resource *i*. The (resource) constrained shortest path problem (CSP) is to determine a shortest path σ in \mathcal{G} from *s* to *t* such that $\sum_{e \in \sigma} r^i(e) \leq \lambda^i$ for $1 \leq i \leq c$.

The CSP problem is NP-complete, even for a single resource constraint [1]. However, if each edge uses a constant unit of that resource (such as the hop count), the CSP problem can be solved in polynomial time, cf. [18], problem ND30. Thus:

Theorem 2. The SE problem for bounded until is in PTIME.

For $h \ge n-1$, it is possible to use Dijkstra's SP algorithm (as for unbounded until), as a shortest path does not contain cycles. If h < n-1, however, Dijkstra's algorithm does not guarantee to obtain a shortest path of at most h hops. We, therefore, adopt the Bellman-Ford (BF) algorithm [8, 15, 11] which fits well to our problem as it proceeds by increasing hop count. It can be readily modified to generate a shortest path within a given hop count. In the sequel of the paper, this algorithm is generalised for computing shortest counterexamples. The BFalgorithm is based on a set of recursive equations; we extend these with the hop count h. For $v \in V$, let $\pi(v, h)$ denote the shortest path from s to v of at most h hops (if it exists). Then:

(s if
$$v = s$$
 and $h \ge 0$; (1a)

$$\pi(v,h) = \begin{cases} \bot & \text{if } v \neq s \text{ and } h = 0; \quad (1b) \\ \arg\min_u \{ d(\pi(u,h-1) \cdot v) \mid (u,v) \in E \} \text{ if } v \neq s \text{ and } h > 0. \quad (1c) \end{cases}$$

where \perp denotes undefined. The last clause states that $\pi(v, h)$ consists of the shortest path to v's predecessor u, i.e., $\pi(u, h-1)$, extended with edge (u, v). Note that $\min_u \{d(\pi(u, h-1) \cdot v) \mid (u, v) \in E\}$ is the distance of the shortest path; by means of arg, the path is obtained. It follows (cf. [24]) that equation (1) characterizes the shortest path from s to v in at most h hops, and can be solved in time $\mathcal{O}(hm)$. As h < n-1, this is indeed in PTIME. Recall that for $h \ge n-1$, Dijkstra's algorithm has a favorable time complexity.

Remark 1. Note that the self-loop of vertex t is neglected when computing the hop-constrained shortest path using BF algorithm. This is because the logic operator is the bounded until $\mathcal{U}^{\leq h}$ instead of point interval until $\mathcal{U}^{=h}$, so that once it reaches t within the hop bound, the path formula holds and the self-loop does not change the path probability.

Example 5. To illustrate the BF algorithm, we compute the shortest path in at most 4 hops from s to t in our example in Fig.2(b), i.e., $\pi(t, 4)$. In order to compute $\pi(t, 4)$, three predecessors of t are considered so that $\pi(t_1, 3)$, $\pi(t_2, 3)$, $\pi(t_3, 3)$ are invoked. Again, to compute $\pi(t_1, 3)$, two predecessors of t_1 are considered so that $\pi(s_1, 2), \pi(s_4, 2)$ are invoked. In sequel, $\pi(s, 1)$ and $\pi(s_3, 1)$ are invoked for $\pi(s_1, 2)$, where $\pi(s, 1)$ is s, defined by equation (1a). $\pi(s_3, 1)$ is derived by invoking its two predecessors $\pi(s, 0)$, which is s (by (1a)) and $\pi(s_1, 0)$ which is \perp (by (1b)). The computation is given in Fig. 3. Note that $\pi(s_4, 2), \pi(s_3, 1), \pi(s, 0), \pi(s_1, 0), \pi(s_3, 0)$ are indicated more than once (with more than one incoming edge), but are (like in dynamic programming) computed only once.

Remark 2. Alternatively, the Viterbi algorithm [16, 29] for probabilistic automata can be applied to our problem. The Viterbi algorithm determines the most probable path that generates a given trace. Let \mathcal{D}' be a DTMC that is obtained after the first step described in Section 4, and suppose that L'(s) contains the set of atomic propositions that are valid in s and all subformulae of the formula under consideration. (Note that these labels are known due to the recursive descent nature of the PCTL model checking algorithm.) Let $tr(\sigma)$ denote the projection of a path $\sigma = s_0 \cdot s_1 \cdot \ldots \cdot s_h$ on its trace γ , i.e., $\gamma = tr(\sigma) = L'(s_0)L'(s_1) \cdots L'(s_h)$. $\sigma \downarrow_i$ denotes the prefix of path σ truncated at length i (thus ending in s_i), formally, $\sigma \downarrow_i = \sigma[0] \cdot \sigma[1] \cdot \ldots \cdot \sigma[i]$. Thus, $tr(\sigma \downarrow_i) = L'(s_0)L'(s_1) \cdots L'(s_i)$. $\gamma \downarrow_i$ denotes



Fig. 3. An example run of the Bellman-Ford algorithm

the prefix of trace γ with length *i*. Let $\rho(\gamma, i, v)$ denote the probability of the most probable path $\sigma \downarrow_i$ whose trace equals $\gamma \downarrow_i$ and reaches state *v*. $\rho(\gamma, i, v)$ can be formally defined as follows:

$$\rho(\gamma, i, v) = \max_{tr(\sigma \downarrow_i) = \gamma_i} \prod_{j=0}^{i-1} \mathbf{P}(s_j, s_{j+1}) \cdot \mathbf{1}_v(s_i),$$

where $\mathbf{1}_{v}(s_{i})$ is the characteristic function of v, i.e., $\mathbf{1}_{v}(s_{i})$ returns 1, if $s_{i} = v$; 0, else.

The Viterbi algorithm provides an algorithmic solution to compute $\rho(\gamma, i, v)$:

$$\rho(\gamma, i, v) = \begin{cases} 1 & \text{if } s = v \text{ and } i = 0; \\ 0 & \text{if } s \neq v \text{ and } i = 0; \\ \max_{u \in S} \rho(\gamma, i - 1, u) \cdot \mathbf{P}(u, v) & \text{otherwise.} \end{cases}$$

By computing $\rho(\Phi^h\Psi, h, s_h)$, the Viterbi algorithm determines the most probable *h*-hop path $\sigma = s_0 \cdot s_1 \cdot \ldots \cdot s_h$ that generates the trace $\gamma = L'(s_0)L'(s_1)\ldots L'(s_h)$ $= \Phi^h\Psi$ with length (h+1). For our SE problem for bounded until, the trace of the most probable hop-constrained path from *s* to *t* is among $\{\Psi at_t, \Phi\Psi at_t, \ldots, \Phi^h\Psi at_t\}$. The self-loop at vertex *t* with probability 1 can make sure that all these paths have length *h*+1 but not change their probabilities, e.g., the path with trace Ψat_t can be extended so that the trace becomes Ψat_t^{h+1} . We obtain the most probable path for $\Phi \mathcal{U}^{\leq h}\Psi$ by computing $\rho((\Phi \lor \Psi \lor at_t)^{h+1}at_t, h+1, t)$ using the Viterbi algorithm. The time complexity of the Viterbi algorithm is $\mathcal{O}(hm)$, as for the BF algorithm.

6 Finding smallest counterexamples

Recall that a smallest (most indicative) counterexample is a counterexample of minimal cardinality, whose probability deviates maximally from the required probability bound. In this section, we investigate algorithms for computing such smallest counterexamples. First observe that any smallest counterexample that contains, say k paths, contains the k most probable paths. This follows from the fact that any non-k most probable path can be exchanged with a more probable path, without changing the size of the counterexample, but by increasing its probability.

6.1 Unbounded until

Lemma 3.1 is applicable here. This suggests to consider the k shortest paths problem.

Definition 10 (KSP problem). Given a weighted digraph $\mathcal{G} = (V, E, w)$, $s, t \in V$, and $k \in \mathbb{N}$, the k shortest paths (KSP) problem is to find k distinct shortest paths between s and t in G, if such paths exist.

Theorem 3. The SC problem for unbounded until is a KSP problem.

Proof. We prove that a smallest counterexample of size k, contains k most probable paths. It is proven by contradiction. Let C be a smallest counterexample for ϕ with |C| = k, and assume C does not contain the k most probable paths satisfying ϕ . Then there is a path $\sigma \notin C$ satisfying ϕ such that $\Pr\{\sigma\} > \Pr\{\sigma'\}$ for some $\sigma' \in C$. Let $C' = C \setminus \{\sigma'\} \cup \{\sigma\}$. Then C' is a counterexample for ϕ , |C| = |C'| and $\Pr(C) > \Pr(C')$. This contradicts C being a smallest counterexample.

The question remains how to obtain k. Various algorithms for the KSP problem require k to be known a priori. This is inapplicable in our setting, as the number of paths in a shortest counterexample is implicitly provided by the probability bound in the PCTL-formula. We therefore consider algorithms that allow to determine k on the fly, i.e., that can halt at any k and resume if necessary. A good candidate is Eppstein's algorithm [14]. Although this algorithm has the best known asymptotic time complexity, viz. $\mathcal{O}(m+n\log n+k)$, in practice the recursive enumeration algorithm (REA) by Jiménez and Marzal [22] prevails. This algorithm has a time complexity in $\mathcal{O}(m+kn\log \frac{m}{n})$ and is based on a generalisation of the recursive equations for the BF-algorithm, and is readily adaptable to the case for bounded h, as we demonstrate below. Note that the time complexity of KSP algorithms depends on k, and as k may be exponential, their complexity is *pseudo*-polynomial.

6.2 Bounded until

Similar to the bounded until case for strongest evidences, we now consider the KSP problem where the length of paths is constrained, as Lemma 3.2 is applicable here.

Definition 11 (HKSP problem). Given a weighted digraph $\mathcal{G} = (V, E, w)$, $s, t \in V$ and $h, k \in \mathbb{N}$, the hop-constrained KSP (HKSP) problem is to determine k shortest paths each of length at most h between s and t.

Similar to Theorem 3 we obtain:

Theorem 4. The SC problem for bounded until is a HKSP problem.

To our knowledge, algorithms for the HKSP problem do not exist. In order to solve the HKSP problem, we propose a new algorithm that is strongly based on Jiménez and Marzal's REA algorithm [22]. The advantage of adapting this algorithm is that k can be determined on the fly, an essential characteristic for our setting. The algorithm is a conservative extension of the REA algorithm.

For $v \in V$, let $\pi^k(v, h)$ denote the k-th shortest path from s to v of length at most h (if it exists). As before, we use \perp to denote the non-existence of a path. We establish the following equations:

$$\pi^{k}(v,h) = \begin{cases} s & \text{if } k = 1, v = s \text{ and } h \ge 0 & (2a) \\ \bot & \text{if } (k > 1, v = s, h = 0) \text{ or } (v \neq s, h = 0) & (2b) \end{cases}$$

where $Q^k(v, h)$ is a set of candidate paths among which $\pi^k(v, h)$ is chosen. The candidate sets are defined by:

$$Q^{k}(v,h) = \begin{cases} \{\pi^{1}(u,h-1)\cdot v \mid (u,v) \in E\} \\ & \text{if } k = 1, v \neq s \text{ or } k = 2, v = s \\ (Q^{k-1}(v,h) - \{\pi^{k'}(u,h-1)\cdot v\}) \cup \{\pi^{k'+1}(u,h-1)\cdot v\} \\ & \text{if } k > 1 \text{ and } u, k' \text{ are the node and index,} \\ & \text{such that } \pi^{k-1}(v,h) = \pi^{k'}(u,h-1)\cdot v \end{cases}$$
(3)

Assume that the path $\pi^{k'+1}(u, h-1) \cdot v = \bot$ if it does not exist, which happens when $Q^{k'+1}(u, h-1) = \emptyset$. Note that $\bot \cdot v = \bot$ for any $v \in V$. $Q^k(v, h) = \emptyset$ if it only contains \bot .

If k=1, the shortest path to v's predecessor u is extended with the edge to v. In the latter clause, $\pi^{k'}(u, h-1)$ denotes the selected (k-1)-st shortest path from s to u, where u is the direct predecessor of v. Paths in $Q^k(v, h)$ for k > 1 are thus either candidate paths for k-1 where the selected path is eliminated (first summand) or the (k'+1)-st shortest path from s to u extended with edge (u, v) (second summand). Note that for the source state s, there is no need to define $Q^k(s, h)$ as $\pi^k(s, h)$ is defined by equations (2a) and (2b), which act as termination conditions.

Proposition 1. The equations (2a)-(2c) and (3) characterize the hop-constrained k shortest paths from s to v in at most h hops.

Proof. Let $\mathcal{R}^k(v,h)$ denote the set of the k shortest paths from s to v in at most h hops. Each path in $\mathcal{R}^k(v,h)$ reaches v from some vertex $u \in Pred(v) = \{w \in V \mid (w,v) \in E\}$. In order to compute $\pi^k(v,h)$, we should consider for every $u \in Pred(v)$, all paths from s to u that do not yield a path in $\mathcal{R}^{k-1}(v,h)$. However, since $k_1 < k_2$ implies that $d(\pi^{k_1}(u,h-1)) + w(u,v) \leq d(\pi^{k_2}(u,h-1)) + w(u,v)$, only the shortest of these paths needs to be taken into account when computing $\pi^k(v,h)$. Thus we can associate to (v,h) a set of candidate paths $Q^k(v,h)$ among which $\pi^k(v,h)$ can be chosen, that contains at most one path for each predecessor $u \in Pred(v)$. This set Q^k is recursively defined by equation (3).

The adapted REA. The adapted REA for computing the k shortest paths from s to t which each consist of at most h hops is sketched as follows. The algorithm is based on the recursive equations given just above.

- i Compute $\pi^1(t,h)$ by the BF algorithm and set k := 1.
- ii Repeat until $\pi^k(t,h)$ does not exist or $\sum_{i=1}^k \Pr\{\pi^i(t,h)\} > p$: (a) Set k := k+1 and compute $\pi^k(t,h)$ by invoking NextPath(v,h,k).

For k>1, and once $\pi^1(v,h), \ldots, \pi^{k-1}(v,h)$ are available, NextPath(t,h,k) computes $\pi^k(v,h)$ as follows:

- 1. If $h \leq 0$, goto step 4.
- 2. If k=2, then set $Q[v,h] := \{\pi^1(u,h-1) \cdot v \mid (u,v) \in E \text{ and } \pi^1(v,h) \neq \pi^1(u,h-1) \cdot v\}.$
- 3. Let u and k' be the node and index such that $\pi^{k-1}(v,h) = \pi^{k'}(u,h-1) \cdot v$. (a) If $\pi^{k'+1}(u, h-1)$ has not yet been computed, invoke NextPath(u, h-1, k'+1).

(b) If $\pi^{k'+1}(u, h-1)$ exists, then insert $\pi^{k'+1}(u, h-1) \cdot v$ in Q[v, h]. 4. If $Q[v, h] \neq \emptyset$, then select and delete a path with minimum weight from Q[v, h] and assign it to $\pi^k(v,h)$, else $\pi^k(v,h)$ does not exist.

In the main program, first the shortest path from s to t is determined using, e.g., the BF-algorithm. The intermediate results are recorded, e.g., all the paths in Fig. 3. Then, the k shortest paths are determined iteratively using the subroutine NextPath. The computation terminates when the k-th shortest path does not exist, or the total probability mass of the k shortest paths so far exceeds the bound p. Recall that p is the lower bound of the PCTL formula to be checked. Note that Q[v,h] in the algorithm corresponds to $Q^k(v,h)$, where k is the parameter of the program. In steps 2 through 3, the set $Q^k(v, h)$ is determined from $Q^{k-1}(v,h)$ according to equation (3). In the final step, $\pi^k(v,h)$ is selected from $Q^k(v,h)$ according to equation (2c).

Example 6. We illustrate how the algorithm progresses by computing 3 shortest paths in Fig. 2 (b) with hop count h = 4, i.e., $\pi^{1}(t, 4)$, $\pi^{2}(t, 4)$ and $\pi^{3}(t, 4)$.

By BF algorithm, we compute $\pi^1(t, 4) = s \cdot s_1 \cdot s_2 \cdot t_2 \cdot t$, several shortest paths to different destinations with different hop constraints are derived as a by-product as we showed in Example 5, where $\pi(v, h)$ in the previous example is $\pi^1(v, h)$ here. We summarize the paths below:

h = 3	h = 2	h = 1	h = 0
		$\pi^1(s,1) = s \cdot s$	$\pi^1(s,0) = s$
$\pi^1(t_1,3) = s \cdot s_1 \cdot t_1$	$\pi^1(s_1,2) = s \cdot s_1$	$\pi^1(s_1,1) = s \cdot s_1$	$\pi^1(s_1,0) = \bot$
$\pi^1(t_2,3) = s \cdot s_1 \cdot s_2 \cdot t_2$	$\pi^1(s_2,2) = s \cdot s_1 \cdot s_2$	$\pi^1(s_2,1) = \bot$	$\pi^1(s_2,0) = \bot$
$\pi^1(t_3,3) = s \cdot s_3 \cdot s_4 \cdot t_3$	$\pi^1(s_4,2) = s \cdot s_3 \cdot s_4$	$\pi^1(s_3,1) = s \cdot s_3$	$\pi^1(s_3,0) = \bot$
		$\pi^1(s_4, 1) = \bot$	$\pi^1(s_4,0) = \bot$

The algorithm for $\pi^2(t, 4)$ is running in Fig. 4.

Note that in order to compute $\pi^2(t, 4)$, the vertices along $\pi^1(t, 4) = s \cdot s_1 \cdot s_2 \cdot t_2 \cdot t_3$ are computed successively, i.e., $\pi^2(t_2,3)$, $\pi^2(s_2,2)$, $\pi^2(s_1,1)$ and $\pi^2(s,0)$, by recursively invoking NextPath. The hop count of each invocation is decreased by 1, so that *NextPath* is invoked 5 times when h = 4 and k = 2. Similarly, to compute $\pi^{3}(t,4)$, the vertices along $\pi^{2}(t,4) = s \cdot s_{3} \cdot s_{4} \cdot t_{1} \cdot t$ ($\pi^{2}(t_{1},3), \pi^{2}(s_{4},2), \pi^{2}(s_{3},1)$ and $\pi^2(s,0)$) are needed. Actually, in this particular example, $\pi^3(t,4)$ can be easily derived, since in Step $3(b)^*$, $d(\pi^1(t_1, 3) \cdot t) = d(\pi^2(t_3, 3) \cdot t)$, then $\pi^3(t, 4)$ definitely equals $\pi^2(t_3, 3) \cdot t$.

$$\begin{split} &k=2, \text{ invoke NextPath}(t,4,2): &/*t_1,t_2,t_3 \text{ are predecessors of } t^*/\\ &3. u=t_2, k'=1, h=3. /* \pi^1(t_3,3)\cdot t_1 = \pi^1(t_2,3)\cdot t_1 = s\cdot s_1\cdot s_2\cdot t_2\cdot t^*/\\ &3(a). \text{ compute } \pi^2(t_2,3) \text{ by invoking NextPath}(t_2,3,2): \\ &2. (k=2) \text{ set } Q[t_2,3] = \{\pi^1(s_4,2)\cdot t_2\}.\\ &3. u=s_2, k'=1, h=2. /* \pi^1(t_2,3) = \pi^1(s_2,2)\cdot t_2 = s\cdot s_1\cdot s_2\cdot t_2 */\\ &3(a). \text{ compute } \pi^2(s_2,2) \text{ by invoking NextPath}(s_2,2,2): \\ &2. (k=2) \text{ set } Q[s_2,2] = \emptyset.\\ &3. u=s_1, k'=1, h=1. /* \pi^1(s_2,2) = \pi^1(s_1,1)\cdot s_2 = s\cdot s_1\cdot s_2 */\\ &3(a). \text{ compute } \pi^2(s_1,1) \text{ by invoking NextPath}(s_1,1,2): \\ &2 (k=2) \text{ set } Q[s_1,1] = \emptyset.\\ &3. u=s, k'=1, h=0. /* \pi^1(s_1,1) = \pi^1(s,0)\cdot s_1 = s\cdot s_1 */\\ &3(a). \text{ compute } \pi^2(s,0) \text{ by invoking NextPath}(s,0,2): \\ &1. \text{ Goto } 4.\\ &4. \pi^2(s,0) = \bot.\\ &3(b). Q[s_1,1] = \emptyset.\\ &4. \pi^2(s_1,1) = \bot.\\ &3(b). Q[s_3,2] = \emptyset.\\ &4. \pi^2(s_2,2) = \bot.\\ &3(b). Q[t_3,3] = \{\pi^1(s_4,2)\cdot t_2\}.\\ &4. \pi^2(t_2,3) = s\cdot s_3\cdot s_4\cdot t_2.\\ &3(b)^*. Q[t,4] = \{\pi^1(t_1,3)\cdot t, \pi^1(t_3,3)\cdot t, \pi^2(t_3,3)\cdot t\}. /* d(\pi^1(t_1,3)\cdot t) = d(\pi^2(t_3,3)\cdot t)^*/\\ &4. \pi^2(t,4) = \pi^1(t_1,3)\cdot t = s\cdot s_3\cdot s_4\cdot t_1\cdot t. /* \pi^1(t_1,3)\cdot t \text{ is the shortest in } Q[t,4] */ \end{split}$$

Fig. 4. An example of the adapted REA

Time complexity. Before we analyze the algorithm time complexity, we first prove that the recursive calls to NextPath to compute $\pi^k(t,h)$ visit, in the worst case, all the vertices in $\pi^{k-1}(t,h)$, which is at most h.

Lemma 4. For k>1 and for all $v \in V$, the computation of $\pi^k(v,h)$ by means of NextPath(v,h,k) may recursively generate calls to NextPath(u,h-1,j) only for vertices u in $\pi^{k-1}(v,h)$.

Proof. Suppose $\pi^{k-1}(v,h) = u_1 \cdot u_2 \cdot \ldots \cdot u_p$, where $u_1 = s$ and $u_p = t$. For every $i = 1, \ldots, p$, let k_i be the index such that $\pi^{k_i}(u_i) = u_1 \cdot u_2 \cdot \ldots \cdot u_i$. Since $\pi^{k-1}(v,h) = \pi^{k_{p-1}}(u_{p-1},h-1) \cdot v$, NextPath(v,h,k) may require a recursive call to $NextPath(u_{p-1},h-1,k_{p-1}+1)$ in case $\pi^{k_{p-1}+1}(u_{p-1},h-1)$ has not been already computed; since $\pi^{k_{p-1}}(u_{p-1},h-1) = \pi^{k_{p-2}}(u_{p-2},h-2) \cdot u_{p-1}$, $NextPath(u_{p-1},h-1,k_{p-1}+1)$ may require a recursive call to $NextPath(u_{p-2},h-2,k_{p-2}+1)$; and so on. In the worst case, the recursive calls extend through the nodes $u_p, u_{p-1}, \ldots, u_1$. If the recursion reaches $\pi^1(s,h')(0 \leq h' \leq h)$ or $\pi^{k'}(v,0)(k'>0, v \neq s)$ or $\pi^{k''}(s,0)(k''>1)$ so that the termination conditions in equation (2a) and (2b) or Algorithm Step 1 hold, then no more recursive calls are performed. □

To determine the computational complexity of the algorithm, we assume the candidate sets to be implemented by heaps (as in [22]). The k shortest paths to a vertex v can be stored in a linked list, where each path $\pi^k(v,h) = \pi^{k'}(u) \cdot v$ is compactly represented by its length and a back pointer to $\pi^{k'}(u)$. Using these data structures, we obtain:

Proposition 2. The time complexity of the adapted REA is $\mathcal{O}(hm+hk\log(\frac{m}{n}))$.

Proof. The computation of the first step takes $\mathcal{O}(hm)$ using the BF-algorithm. Due to Lemma 4, the number of recursive invocations to *NextPath* is bounded by

h, the maximum length of $\pi^{k-1}(t, h)$. At any given time, the set $Q^k(v, h)$ contains at most |Pred(v)| paths where $Pred(v) = \{u \mid (u, v) \in E\}$, i.e., one path for each predecessor vertex of v. By using heaps to store the candidate sets, a minimal element can be determined and deleted (cf. Step4) in $\mathcal{O}(\log |Pred(v)|)$ time. Insertion of a path (as in Steps 2 and 3(b)) takes the same time complexity. Since $\sum_{v \in V} |Pred(v)| = m$, $\sum_{v \in V} \log |Pred(v)|$ is maximized when all vertices have an equal number of predecessors, i.e., $|Pred(v)| = \frac{m}{n}$. Hence, it takes $\mathcal{O}(h \log(\frac{m}{n}))$ to compute $\pi^k(v, h)$. We have k such paths to compute, yielding $\mathcal{O}(hm+hk \log(\frac{m}{n}))$.

Note that the time complexity is pseudo-polynomial due to the dependence on k which may be exponential in n. As in our setting, k is not known in advance, this can not be reduced to a polynomial time complexity.

7 Conclusion

Summary of results. We have investigated the computation of strongest evidences (maximally probable paths) and smallest counterexamples for PCTL model checking of DTMCs. Relationships to various kinds of shortest path problems have been established. Summarizing we have obtained:

counterexample problem	shortest path problem	time complexity
SE (until) SE (bounded until) SC (until)	SP HSP KSP	$\mathcal{O}(m+n\log n)$ $\mathcal{O}(hm)$ $\mathcal{O}(m+n\log n+k)$ $\mathcal{O}(k+n\log n+k)$

where n and m are the number of states and transitions, h is the hop bound, and k is the number of shortest paths.

For DTMCs with rewards, we can establish along the same lines as in this paper that determining strongest evidences for violating reward- and hop-bounded until-formulae boils down to solving a non-trivial instance of the CSP problem. As this problem is NP complete, efficient algorithms for finding counterexamples for PRCTL [4] will be hard to obtain.

Further research. Topics for further research are: experimental research of the proposed algorithms in probabilistic model checking, considering loopless paths (see e.g., [21, 25, 19]), and extension towards continuous-time models.

Related work. With the notable exception of [2, 3], counterexample generation for probabilistic model checking has not been addressed before. Aljazzar *et al.* [2] consider the generation of a most probable path for timed reachability in CTMCs. They map this onto a bounded-until problem on DTMCs, and use heuristics (Z^{*}) for determining the most probable path. Unbounded until is not considered, and neither a correctness proof nor complexity results are provided. Recently, [3] generalises this heuristic-based approach for CTMCs to obtain failure subgraphs, i.e., counterexamples. To our knowledge, smallest counterexamples have not been considered yet.

Acknowledgement. This research has been performed as part of the QUPES project that is financed by the Netherlands Organization for Scientific Research (NWO). David N. Jansen is kindly acknowledged for remarks on an earlier version of this paper.

References

- R.K. Ahuja, T.L. Magnanti and J.B. Orlin. Network Flows: Theory, Algorithms and Applications, Prentice Hall, Inc., 1993.
- H. Aljazzar, H. Hermanns and S. Leue. Counterexamples for timed probabilistic reachability. FORMATS 2005, LNCS 3829: 177-195, 2005.
- 3. H. Aljazzar and S. Leue. Extended directed search for probabilistic timed reachability. FORMATS 2006. (to appear)
- S. Andova, H. Hermanns and J.-P. Katoen. Discrete-time rewards model-checked. FOR-MATS 2003, LNCS 2791: 88-104, 2003.
- C. Baier, J.-P. Katoen, H. Hermanns and V. Wolf. Comparative branching-time semantics for Markov chains. *Inf. Comput.* 200(2): 149-214 (2005).
- T. Ball, M. Naik and S. K. Rajamani. From symptom to cause: localizing errors in counterexample traces. POPL: 97-105, 2003.
- G. Behrmann, K. G. Larsen and J. I. Rasmussen. Optimal scheduling using priced timed automata. ACM SIGMETRICS Perf. Ev. Review 32(4): 34-40 (2005).
- 8. R. Bellman. On a routing problem. Quarterly of Appl. Math., 16(1): 87-90 (1958).
- 9. E.M. Clarke, O. Grumberg, S. Jha, Y. Lu and H. Veith: Counterexample-guided abstraction refinement. CAV, LNCS 1855: 154-169, 2000.
- E.M. Clarke, S. Jha, Y. Lu and H. Veith. Tree-like counterexamples in model checking. LICS: 19-29 (2002).
- T.H. Cormen, C.E. Leiserson, R.L. Rivest and C. Stein. Introduction to Algorithms, 2001. Section 24.1: The Bellman-Ford algorithm, pp.588-592.
- L. de Alfaro, T.A. Henzinger and F. Mang. Detecting errors before reaching them. CAV, LNCS 2725: 186-201, 2000.
- 13. E.W. Dijkstra. A note on two problems in connection with graphs. *Num. Math.*, 1:395-412 (1959).
- 14. D. Eppstein. Finding the k shortest paths. SIAM J. Comput. 28(2): 652-673 (1998).
- 15. L.R. Ford jr. and D.R. Fulkerson. Flows in Networks, Princeton Univ. Press, 1962.
- 16. G.D. Forney. The Viterbi algorithm. Proc. of the IEEE 61(3): 268-278 (1973).
- B. L. Fox. k-th shortest paths and applications to the probabilistic networks. In ORSA/TIMS National Mtg, volume 23, page B263. Bull. Operations Research Soc. of America, 1975.
- M.R. Garey and D.S. Johnson. Computers and Intractability, A Guide to the Theory of NP-Completeness, Freeman, San Francisco, 1979.
- E. Hadjiconstantinou and N. Christofides. An efficient implementation of an algorithm for finding K shortest simple paths. *Networks* 34(2): 88-101 (1999).
- H. Hansson and B. Jonsson. A logic for reasoning about time and reliability. Formal Asp. Comput. 6(5): 512-535 (1994).
- J. Hershberger, M. Maxel and S. Suri. Finding the k shortest simple paths: A new algorithm and its implementation. ALENEX 2003, in Proc. of the Fifth Workshop on Algorithm Engineering and Experiments, Baltimore, USA, pp. 26-36, 2003.
- 22. V.M. Jiménez and A. Marzal. Computing the K shortest paths: A new algorithm and an experimental comparison. WAE 1999, LNCS 1668: 15-29, 1999.
- H. Jin, K. Ravi and F. Somenzi. Fate and free will in error traces. STTT 6(2): 102-116 (2004).
- 24. E.L. Lawler. Combinatorial Optimization: Networks and Matroids. Holt, Reinhart, and Winston, 1976.
- E.Q.V. Martins and M.M.B. Pascoal. A new implementation of Yen's ranking loopless paths algorithm. 4OR 1(2): 121-133 (2003).
- E.Q.V. Martins, M.M.B. Pascoal and J.L.E. Dos Santos. Deviation algorithms for ranking shortest paths. Int. J. Found. Comput. Sci. 10(3): 247-262 (1999).
- K. Mehlhorn and M. Ziegelmann. Resource constrained shortest paths. ESA 2000, LNCS 1879: 326-337, 2000.
- S. Shoham and O. Grumberg. A game-based framework for CTL counterexamples and 3-valued abstraction-refinement. CAV, LNCS 2725: 275-287, 2003.
- E. Vidal, F. Thollard, C. de la Higuera, F. Casacuberta and R.C. Carrasco. Probabilistic finite-state machines-Part I. *IEEE Trans. Pattern Anal. Mach. Intell.* 27(7): 1013-1025 (2005).

Aachener Informatik-Berichte

This is a list of recent technical reports. To obtain copies of technical reports please consult http://aib.informatik.rwth-aachen.de/ or send your request to: Informatik-Bibliothek, RWTH Aachen, Ahornstr. 55, 52056 Aachen, Email: biblio@informatik.rwth-aachen.de

1987-01 *	Fachgruppe Informatik: Jahresbericht 1986
1987-02 *	David de Frutos Escrig, Klaus Indermark: Equivalence Relations of Non-
	Deterministic Ianov-Schemes
1987-03 *	Manfred Nagl: A Software Development Environment based on Graph
	Technology
1987-04 *	Claus Lewerentz, Manfred Nagl, Bernhard Westfechtel: On Integration
	Mechanisms within a Graph-Based Software Development Environment
1987-05 *	Reinhard Rinn: Über Eingabeanomalien bei verschiedenen Inferenzmod-
	ellen
1987-06 *	Werner Damm, Gert Döhmen: Specifying Distributed Computer Archi-
	tectures in $AADL^*$
1987-07 *	Gregor Engels, Claus Lewerentz, Wilhelm Schäfer: Graph Grammar En-
	gineering: A Software Specification Method
1987-08 *	Manfred Nagl: Set Theoretic Approaches to Graph Grammars
1987-09 *	Claus Lewerentz, Andreas Schürr: Experiences with a Database System
	for Software Documents
1987-10 *	Herbert Klaeren, Klaus Indermark: A New Implementation Technique
	for Recursive Function Definitions
1987-11 *	Rita Loogen: Design of a Parallel Programmable Graph Reduction Ma-
	chine with Distributed Memory
1987-12	J. Börstler, U. Möncke, R. Wilhelm: Table compression for tree automata
1988-01 *	Gabriele Esser, Johannes Rückert, Frank Wagner Gesellschaftliche As-
	pekte der Informatik
1988-02 *	Peter Martini, Otto Spaniol: Token-Passing in High-Speed Backbone
	Networks for Campus-Wide Environments
1988-03 *	Thomas Welzel: Simulation of a Multiple Token Ring Backbone
1988-04 *	Peter Martini: Performance Comparison for HSLAN Media Access Pro-
1000 05 *	tocols
1988-05 *	Peter Martini: Performance Analysis of Multiple Token Rings
1988-06 *	Andreas Mann, Johannes Ruckert, Otto Spaniol: Datenfunknetze
1988-07	Andreas Mann, Johannes Ruckert: Packet Radio Networks for Data Ex-
1000 00 *	change
1988-08	Andreas Mann, Jonannes Ruckert: Concurrent Slot Assignment Protocol
1000 00 *	IOF Packet Radio Networks
1988-09	w. Kremer, F. Reichert, J. Ruckert, A. Mann: Entwurf einer Netzw-
	Streßenverkehre
1000 10 *	Strabenverkenrs Kai Jakaba, Tawanda Haan Eviendhy Natwonking
1900-1U 1088 11 *	Kai Jakobs: Towards User-Friendry Networking Kai Jakobs: The Directory Evolution of a Standard
1900-11 1088 19 *	Kai Jakobs: Directory Sorvices in Distributed Systems A Survey
1088_12 *	Martine Schümmer: RS-511 a Protocol for the Plant Floor
1900-19	marine senumer. no-orr, a riotocor for the riant riot

1988-14 *	U. Quernheim: Satellite Communication Protocols - A Performance Comparison Considering On Board Processing
1088 15 *	Poter Martini Otto Spaniol, Thomas Walzel: File Transfer in High Speed
1900-10	Token Ring Networks: Performance Evaluation by Approximate Analysis
1088 16 *	Enchgruppo Informatik: Jahroshoricht 1087
1988-10	Welfgang Thomas: Automata on Infinite Objects
1900-17	Michael Sonnongsheim, On Detri Nets and Deta Flow Craphs
1900-10	Heiles Verler, Euroticnel Distribution of the Contentual Analysis in
1988-19	Block-Structured Programming Languages: A Case Study of Tree Trans- ducers
1088-20 *	Thomas Welzel: Fineatz des Simulationswerkzeuges ONAP2 zur Leis-
1900-20	tungsbewertung von Kommunikationsprotokollon
1000 01 *	The Japping C. Lowerentz: Integrated Project Team Management in a
1900-21	The Jamming, C. Lewelentz: Integrated Project Team Management in a
1000 00 *	Software Development Environment
1988-22	Joost Engelfriet, Heiko Vogler: Modular Tree Transducers
1988-23 *	Wolfgang Thomas: Automata and Quantifier Hierarchies
1988-24 *	Uschi Heuter: Generalized Definite Tree Languages
1989-01 *	Fachgruppe Informatik: Jahresbericht 1988
1989-02 *	G. Esser, J. Rückert, F. Wagner (Hrsg.): Gesellschaftliche Aspekte der
	Informatik
1989-03 *	Heiko Vogler: Bottom-Up Computation of Primitive Recursive Tree
	Functions
1989-04 *	Andy Schürr: Introduction to PROGRESS, an Attribute Graph Gram-
	mar Based Specification Language
1989-05	J. Börstler: Reuse and Software Development - Problems, Solutions, and
	Bibliography (in German)
1989-06 *	Kai Jakobs: OSI - An Appropriate Basis for Group Communication?
1989-07 *	Kai Jakobs: ISO's Directory Proposal - Evolution, Current Status and Future Problems
1989-08 *	Bernhard Westfechtel: Extension of a Graph Storage for Software Doc- uments with Primitives for Undo/Redo and Revision Control
1989-09 *	Peter Martini: High Speed Local Area Networks - A Tutorial
1989-10 *	P. Davids, Th. Welzel: Performance Analysis of DQDB Based on Simulation
1989-11 *	Manfred Nagl (Ed.): Abstracts of Talks presented at the WG '89 15th International Workshop on Graphtheoretic Concepts in Computer Sci- ence
1989-12 *	Peter Martini: The DQDB Protocol - Is it Playing the Game?
1989-13 *	Martine Schümmer: CNC/DNC Communication with MAP
1989-14 *	Martine Schümmer: Local Area Networks for Manufactoring Environ-
	ments with hard Real-Time Requirements
1989-15 *	M. Schümmer, Th. Welzel, P. Martini: Integration of Field Bus and
	MAP Networks - Hierarchical Communication Systems in Production
1080 16 *	C. Vosson K. II. Witt: SUXESS: Towards a Sound Unification of Ex.
1303-10	tansions of the Relational Data Model
	tensions of the Relational Data Model

1989-17 *	J. Derissen, P. Hruschka, M.v.d. Beeck, Th. Janning, M. Nagl: Integrat-
	ing Structured Analysis and Information Modelling
1989-18	A. Maassen: Programming with Higher Order Functions
1989-19 *	Mario Rodriguez-Artalejo, Heiko Vogler: A Narrowing Machine for Syn- tax Directed BABEL
1989-20	H. Kuchen, R. Loogen, J.J. Moreno Navarro, M. Rodriguez Artalejo: Graph-based Implementation of a Functional Logic Language
1990-01 *	Fachgruppe Informatik: Jahresbericht 1989
1990-02 *	Vera Jansen, Andreas Potthoff, Wolfgang Thomas, Udo Wermuth: A Short Guide to the AMORE System (Computing Automata, MOnoids and Regular Expressions)
1990-03 *	Jerzy Skurczynski: On Three Hierarchies of Weak SkS Formulas
1990-04	R. Loogen: Stack-based Implementation of Narrowing
1990-05	H. Kuchen, A. Wagener: Comparison of Dynamic Load Balancing Strate- gies
1990-06 *	Kai Jakobs, Frank Reichert: Directory Services for Mobile Communica- tion
1990-07 *	Kai Jakobs: What's Beyond the Interface - OSI Networks to Support Cooperative Work
1990-08 *	Kai Jakobs: Directory Names and Schema - An Evaluation
1990-09 *	Ulrich Quernheim, Dieter Kreuer: Das CCITT - Signalisierungssystem
1000 11	Nr. 7 auf Satellitenstrecken; Simulation der Zeichengabestrecke
1990-11	H. Kuchen, R. Loogen, J.J. Moreno Navarro, M. Rodriguez Artalejo: Lazy Narrowing in a Graph Machine
1990-12 *	Kai Jakobs, Josef Kaltwasser, Frank Reichert, Otto Spaniol: Der Computer fährt mit
1990-13 *	Rudolf Mathar, Andreas Mann: Analyzing a Distributed Slot Assignment Protocol by Markov Chains
1990-14	A. Maassen: Compilerentwicklung in Miranda - ein Praktikum in funk- tionaler Programmierung (written in german)
1990-15 *	Manfred Nagl, Andreas Schürr: A Specification Environment for Graph Grammars
1990-16	A. Schürr: PROGRESS: A VHL-Language Based on Graph Grammars
1990-17 *	Marita Möller: Ein Ebenenmodell wissensbasierter Konsultationen - Un- terstützung für Wissensakouisition und Erklärungsfähigkeit
1990-18 *	Eric Kowalewski: Entwurf und Interpretation einer Sprache zur Beschrei- hung von Kongultationgnhagen in Expertengustemen
1990-20	Y. Ortega Mallen, D. de Frutos Escrig: A Complete Proof System for
1990-21 *	Manfred Nagl: Modelling of Software Architectures: Importance, No-
1990-22	tions, Experiences H. Fassbender, H. Vogler: A Call-by-need Implementation of Syntax Di- rected Functional Programming
1991-01	Guenther Geiler (ed.), Fachgruppe Informatik, Jahresbericht 1990
1991-03	B. Steffen, A. Ingolfsdottir: Characteristic Formulae for Processes with
1991-04	M. Portz: A new class of cryptosystems based on interconnection net- works

1991-05	H. Kuchen, G. Geiler: Distributed Applicative Arrays
1991-06 *	Ludwig Staiger: Kolmogorov Complexity and Hausdorff Dimension
1991-07 *	Ludwig Staiger: Syntactic Congruences for w-languages
1991-09 *	Eila Kuikka: A Proposal for a Syntax-Directed Text Processing System
1991-10	K. Gladitz, H. Fassbender, H. Vogler: Compiler-based Implementation
	of Syntax-Directed Functional Programming
1991-11	R. Loogen, St. Winkler: Dynamic Detection of Determinism in Func-
	tional Logic Languages
1991-12 *	K. Indermark, M. Rodriguez Artaleio (Eds.): Granada Workshop on the
	Integration of Functional and Logic Programming
1991-13 *	Rolf Hager, Wolfgang Kremer: The Adaptive Priority Scheduler: A More
	Fair Priority Service Discipline
1991-14 *	Andreas Fashender Wolfgang Kremer: A New Approximation Algorithm
1001 11	for Tandem Networks with Priority Nodes
1991-15	J Börstler A Zündorf: Revisiting extensions to Modula-2 to support
1001 10	reusability
1991-16	I Börstler Th Janning Bridging the gap between Requirements Anal-
1001 10	vsis and Design
1991-17	A Zündorf A Schürr: Nondeterministic Control Structures for Graph
1001 11	Rewriting Systems
1991-18 *	Matthias Jarke, John Mylopoulos, Joachim W. Schmidt, Yannis Vassil-
1001 10	iou: DAIDA: An Environment for Evolving Information Systems
1991-19	M. Jeusfeld, M. Jarke: From Relational to Object-Oriented Integrity
1001 10	Simplification
1991-20	G. Hogen, A. Kindler, R. Loogen: Automatic Parallelization of Lazy
	Functional Programs
1991-21 *	Prof. Dr. rer. nat. Otto Spaniol: ODP (Open Distributed Processing):
	Yet another Viewpoint
1991-22	H. Kuchen, F. Lücking, H. Stoltze: The Topology Description Language
	TDL
1991-23	S. Graf, B. Steffen: Compositional Minimization of Finite State Systems
1991-24	R. Cleaveland, J. Parrow, B. Steffen: The Concurrency Workbench: A
	Semantics Based Tool for the Verification of Concurrent Systems
1991-25 *	Rudolf Mathar, Jürgen Mattfeldt: Optimal Transmission Ranges for Mo-
	bile Communication in Linear Multihop Packet Radio Networks
1991-26	M. Jeusfeld, M. Staudt: Query Optimization in Deductive Object Bases
1991-27	J. Knoop, B. Steffen: The Interprocedural Coincidence Theorem
1991-28	J. Knoop, B. Steffen: Unifying Strength Reduction and Semantic Code
	Motion
1991-30	T. Margaria: First-Order theories for the verification of complex FSMs
1991-31	B. Steffen: Generating Data Flow Analysis Algorithms from Modal Spec-
	ifications
1992-01	Stefan Eherer (ed.), Fachgruppe Informatik: Jahresbericht 1991
1992-02 *	Bernhard Westfechtel: Basismechanismen zur Datenverwaltung in struk-
	turbezogenen Hypertextsystemen
1992-04	S. A. Smolka, B. Steffen: Priority as Extremal Probability
1992-05 *	Matthias Jarke, Carlos Maltzahn, Thomas Rose: Sharing Processes:
	Team Coordination in Design Repositories

1992-06	O. Burkart, B. Steffen: Model Checking for Context-Free Processes
1992-07 *	Matthias Jarke, Klaus Pohl: Information Systems Quality and Quality
	Information Systems
1992-08 *	Rudolf Mathar, Jürgen Mattfeldt: Analyzing Routing Strategy NFP in
	Multihop Packet Radio Networks on a Line
1992-09 *	Alfons Kemper, Guido Moerkotte: Grundlagen objektorientierter Daten-
	banksysteme
1992-10	Matthias Jarke, Manfred Jeusfeld, Andreas Miethsam, Michael Gocek:
	Towards a logic-based reconstruction of software configuration manage-
	ment
1992-11	Werner Hans: A Complete Indexing Scheme for WAM-based Abstract
	Machines
1992-12	W. Hans, R. Loogen, St. Winkler: On the Interaction of Lazy Evaluation
	and Backtracking
1992-13 *	Matthias Jarke, Thomas Rose: Specification Management with CAD
1992-14	Th. Noll, H. Vogler: Top-down Parsing with Simultaneous Evaluation on
	Noncircular Attribute Grammars
1992-15	A. Schuerr, B. Westfechtel: Graphgrammatiken und Graphersetzungssys-
	teme(written in german)
1992-16 *	Graduiertenkolleg Informatik und Technik (Hrsg.): Forschungsprojekte
	des Graduiertenkollegs Informatik und Technik
1992-17	M. Jarke (ed.): ConceptBase V3.1 User Manual
1992-18 *	Clarence A. Ellis, Matthias Jarke (Eds.): Distributed Cooperation in
	Integrated Information Systems - Proceedings of the Third International
	Workshop on Intelligent and Cooperative Information Systems
1992-19-00	H. Kuchen, R. Loogen (eds.): Proceedings of the 4th Int. Workshop on
	the Parallel Implementation of Functional Languages
1992-19-01	G. Hogen, R. Loogen: PASTEL - A Parallel Stack-Based Implementation
	of Eager Functional Programs with Lazy Data Structures (Extended
	Abstract)
1992-19-02	H. Kuchen, K. Gladitz: Implementing Bags on a Shared Memory MIMD-
1000 10 00	Machine
1992-19-03	C. Rathsack, S.B. Scholz: LISA - A Lazy Interpreter for a Full-Fledged
	Lambda-Calculus
1992-19-04	T.A. Bratvold: Determining Useful Parallelism in Higher Order Func-
1000 10 05	
1992-19-05	S. Kahrs: Polymorphic Type Checking by Interpretation of Code
1992-19-06	M. Chakravarty, M. Kohler: Equational Constraints, Residuation, and
1000 10 07	the Parallel JUMP-Machine
1992-19-07	J. Seward: Polymorphic Strictness Analysis using Frontiers (Draft Ver-
1000 10 00	SIOII) D. Gürtarez A. Kimme W. Klenne zi Delât - A. Gerezilizz Grezil
1992-19-08	D. Gartner, A. Kimms, W. Kluge: pl-Red + - A Compliing Graph-
1000 10 00	D. Harry, C. Durry, For a run Fledged Lambda-Calculus
1992-19-09	D. Howe, G. Burn: Experiments with strict SIG code
1992-19-10	5. Gradert: raraner implementation of runctional Languages Using
1002 10 11	M Joy T Axford: A Parallol Craph Poduction Machine
1002-10-11	A Bonnett P Kelly Simulation of Multicache Parallel Reduction
1332-13-12	A. Demiett, I. Keny. Simulation of Multicache Parallel Reduction

1992-19-13	K. Langendoen, D.J. Agterkamp: Cache Behaviour of Lazy Functional Programs (Working Paper)
1992-19-14	K. Hammond, S. Peyton Jones: Profiling scheduling strategies on the GBIP parallel reducer
1992-19-15	S. Mintchey: Using Strictness Information in the STG-machine
1992-19-16	D Rushall: An Attribute Grammar Evaluator in Haskell
1992-19-17	I Wild H Glaser P Hartel: Statistics on storage management in a lazy
1992-19-11	functional language implementation
1992-19-18	W.S. Martins: Parallel Implementations of Functional Languages
1992-19-19	D. Lester: Distributed Garbage Collection of Cyclic Structures (Draft version)
1992-19-20	J.C. Glas, R.F.H. Hofman, W.G. Vree: Parallelization of Branch-and-
	Bound Algorithms in a Functional Programming Environment
1992-19-21	S. Hwang, D. Rushall: The nu-STG machine: a parallelized Spineless
	Tagless Graph Reduction Machine in a distributed memory architecture (Draft version)
1992-19-22	G. Burn, D. Le Metayer: Cps-Translation and the Correctness of Opti-
1000 10 00	mising Compilers
1992-19-23	S.L. Peyton Jones, P. Wadler: Imperative functional programming (Brief summary)
1992-19-24	W. Damm, F. Liu, Th. Peikenkamp: Evaluation and Parallelization of
	Functions in Functional + Logic Languages (abstract)
1992-19-25	M. Kesseler: Communication Issues Regarding Parallel Functional Graph
1002 10 26	The Poikankamp: Charakterizing and corresponding neededness in fune
1992-19-20	tional loginc languages (abstract)
1992-19-27	H. Doerr: Monitoring with Graph-Grammars as formal operational Models
1992-19-28	J van Groningen: Some implementation aspects of Concurrent Clean on
1002 10 20	distributed memory architectures
1992-19-29	G. Ostheimer: Load Bounding for Implicit Parallelism (abstract)
1992-20	H. Kuchen, F.J. Lopez Fraguas, J.J. Moreno Navarro, M. Rodriguez
	Artalejo: Implementing Disequality in a Lazy Functional Logic Language
1992-21	H. Kuchen, F.J. Lopez Fraguas: Result Directed Computing in a Func-
	tional Logic Language
1992-22	H Kuchen J.J. Moreno Navarro M.V. Hermenegildo: Independent
1002 22	AND-Parallel Narrowing
1002-23	T Margaria B Staffan: Distinguishing Formulas for Free
1002 24	K Pohl: The Three Dimensions of Requirements Engineering
1002 25 *	R. Foin. The Three Dimensions of Requirements Engineering
1992-20	nications
1992-26 *	Michael von der Beeck: Integration of Structured Analysis and Timed
	Statecharts for Real-Time and Concurrency Specification
1992-27	W. Hans, St. Winkler: Aliasing and Groundness Analysis of Logic Pro-
	grams through Abstract Interpretation and its Safety
1992-28 *	Gerhard Steinke Matthias Jarke: Support for Security Modeling in In-
1002-20	formation Systems Design
1002 20	B. Schinzol: Warum Frauenfarschung in Naturwissonschaft und Tachril
1334-49	D. Sommen. Warum Fragemoischung in Naturwissenschaft und Technik

1992-30	A. Kemper, G. Moerkotte, K. Peithner: Object-Orientation Axiomatised
1009 29 *	by Dynamic Logic Bound Heinniche, Kei Jelseber Timer Hendling in High Deufermenee
1992-32	Transport Systems
1992-33 *	B. Heinrichs, K. Jakobs, K. Lenßen, W. Reinhardt, A. Spinner: Euro-
1002 00	Bridge: Communication Services for Multimedia Applications
1992-34	C. Gerlhof, A. Kemper, Ch. Kilger, G. Moerkotte: Partition-Based Clus-
	tering in Object Bases: From Theory to Practice
1992-35	J. Börstler: Feature-Oriented Classification and Reuse in IPSEN
1992-36	M. Jarke, J. Bubenko, C. Rolland, A. Sutcliffe, Y. Vassiliou: Theories Un-
	derlying Requirements Engineering: An Overview of NATURE at Gen-
	esis
1992-37 *	K. Pohl, M. Jarke: Quality Information Systems: Repository Support for
	Evolving Process Models
1992-38	A. Zuendorf: Implementation of the imperative / rule based language
	PROGRES
1992-39	P. Koch: Intelligentes Backtracking bei der Auswertung funktional-
	logischer Programme
1992-40 *	Rudolf Mathar, Jürgen Mattfeldt: Channel Assignment in Cellular Radio
	Networks
1992-41 *	Gerhard Friedrich, Wolfgang Neidl: Constructive Utility in Model-Based
	Diagnosis Repair Systems
1992-42 *	P. S. Chen, R. Hennicker, M. Jarke: On the Retrieval of Reusable Soft-
1000 40	ware Components
1992-43	W. Hans, St. Winkler: Abstract Interpretation of Functional Logic Lan-
1009 44	guages
1992-44	N. Klesel, A. Schuerr, B. Westlechtel: Design and Evaluation of GRAS,
1002_01 *	Fachgruppe Informatik: Jahresbericht 1002
1993-02 *	Patrick Shicheng Chen: On Inference Bules of Logic-Based Information
1000 02	Retrieval Systems
1993-03	G. Hogen, R. Loogen: A New Stack Technique for the Management of
	Runtime Structures in Distributed Environments
1993-05	A. Zündorf: A Heuristic for the Subgraph Isomorphism Problem in Ex-
	ecuting PROGRES
1993-06	A. Kemper, D. Kossmann: Adaptable Pointer Swizzling Strategies in
	Object Bases: Design, Realization, and Quantitative Analysis
1993-07 *	Graduiertenkolleg Informatik und Technik (Hrsg.): Graduiertenkolleg In-
	formatik und Technik
1993-08 *	Matthias Berger: k-Coloring Vertices using a Neural Network with Con-
	vergence to Valid Solutions
1993-09	M. Buchheit, M. Jeusfeld, W. Nutt, M. Staudt: Subsumption between
	Queries to Object-Oriented Databases
1993-10	O. Burkart, B. Steffen: Pushdown Processes: Parallel Composition and
	Model Checking
1993-11 *	R. Große-Wienker, O. Hermanns, D. Menzenbach, A. Pollacks, S. Repet-
	zki, J. Schwartz, K. Sonnenschein, B. Westfechtel: Das SUKITS-Projekt:
	A-posteriori-Integration heterogener CIM-Anwendungssysteme

1993-12 *	Rudolf Mathar, Jürgen Mattfeldt: On the Distribution of Cumulated
1003 13	O Malor I Staiger: On Syntactic Congruences for emerge languages
1993-13	M. Jarka, St. Fharar, R. Callaradoorfar, M. Jausfald, M. Staudt: Con
1993-14	M. Jarke, St. Enerer, R. Ganersdoener, M. Jeusleid, M. Staudt. Con-
1002 15	M Standt H.W. Nissen, M.A. Lausfeld, Oscara ha Class, Dala and Cara
1993-15	M. Staudt, H. W. Nissen, M.A. Jeusield: Query by Class, Rule and Con-
1002 16 *	Cept M. Janka K. Dahl St. Jacobs et al. Decuirements Engineering: An In-
1995-10	M. Jarke, K. Polin, St. Jacobs et al.: Requirements Engineering: An in-
1002 17 *	M Jarka K Dahl Establishing Vision in Contant.
1995-17	M. Jarke, K. Polit: Establishing vision in Context: Towards a Model of
1002 10	W Hang H Kuchen St Winkley Full Indexing for Lagy Nerroring
1995-18	W. Hans, H. Kuchen, St. Winkler: Full Indexing for Lazy Narrowing
1993-19	W. Hans, J.J. Ruz, F. Saenz, St. Winkier: A VHDL Specification of a
1002 20 *	Shared Memory Parallel Machine for Babel
1993-20	K. Flike, M. Jarke, P. Szczurko, R. Soltysiak: Quality Management for
1002 91	Expert Systems in Process Control M. Janka, M.A. Jaugfeld, D. Szerunka: Three Agnesits of Intelligent Co.
1995-21	M. Jarke, M.A. Jeusleid, P. Szczurko: Three Aspects of Intelligent Co-
1004 01	Margit Congret Strep Martin (ada) Eachgruppe Informatile Jahren
1994-01	hargit Generet, Sven Martin (eds.), Facingruppe informatik: Jahres-
1004 02	M. Lafaving: Development of Incremental Integration Teole Using Formal
1994-02	Specifications
1004 02 *	D Constantanoulos M Jarko I Mulanoulos V Vassilious The Software
1994-05	Information Base: A Server for Baue
1004 04 *	Rolf Hager Budolf Mether Jürgen Mettfeldt: Intelligent Cruise Control
1994-04	and Poliable Communication of Mobile Stations
1004 05 *	Rolf Hager, Poter Hermesmann, Michael Portz: Fossibility of Authonti
1334-00	ention Procedures within Advanced Transport Telematics
1004 06 *	Claudia Popion Bornd Mover Aval Kuopper: A Formal Approach to
1334-00	Service Import in ODP Trader Federations
1004-07	P Paters P Szczurko: Integrating Models of Quality Management Meth-
1554-01	ods by an Object-Oriented Repository
1994-08 *	Manfred Nagl Bernhard Westfechtel: A Universal Component for the
1554-00	Administration in Distributed and Integrated Development Environ-
	ments
1994-09 *	Patrick Horster Holger Petersen: Signatur, und Authentifikationsver-
1001 00	fahren auf der Basis des diskreten Logarithmusproblems
1994-11	A Schürr: PROGRES A Visual Language and Environment for PRO-
1001 11	gramming with Graph REwrite Systems
1994-12	A. Schürr: Specification of Graph Translators with Triple Graph Gram-
100112	mars
1994-13	A. Schürr: Logic Based Programmed Structure Rewriting Systems
1994-14	L. Staiger: Codes, Simplifying Words, and Open Set Condition
1994-15 *	Bernhard Westfechtel: A Graph-Based System for Managing Configura-
-	tions of Engineering Design Documents
1994-16	P. Klein: Designing Software with Modula-3
1994-17	I. Litovsky, L. Staiger: Finite acceptance of infinite words

1994-18	G. Hogen, R. Loogen: Parallel Functional Implementations: Graphbased
1004 10	vs. Stackbased Reduction
1994-19	M. Jeusfeld, U. Johnen: An Executable Meta Model for Re-Engineering of Database Schemas
1004-20 *	B Gallersdörfer M Jarke K Klabunde Intelligent Networks as a Data
1334-20	Intensive Application (INDIA)
1994-21	M Mohnen: Proving the Correctness of the Static Link Technique Using
1001 21	Evolving Algebras
1994-22	H. Fernau, L. Staiger: Valuations and Unambiguity of Languages, with
	Applications to Fractal Geometry
1994-24 *	M. Jarke, K. Pohl, R. Dömges, St. Jacobs, H. W. Nissen: Requirements
	Information Management: The NATURE Approach
1994-25 *	M. Jarke, K. Pohl, C. Rolland, JR. Schmitt: Experience-Based Method
	Evaluation and Improvement: A Process Modeling Approach
1994-26 *	St. Jacobs, St. Kethers: Improving Communication and Decision Making
	within Quality Function Deployment
1994-27 *	M. Jarke, H. W. Nissen, K. Pohl: Tool Integration in Evolving Informa-
	tion Systems Environments
1994-28	O. Burkart, D. Caucal, B. Steffen: An Elementary Bisimulation Decision
	Procedure for Arbitrary Context-Free Processes
1995-01 *	Fachgruppe Informatik: Jahresbericht 1994
1995-02	Andy Schürr, Andreas J. Winter, Albert Zündorf: Graph Grammar En-
	gineering with PROGRES
1995-03	Ludwig Staiger: A Tight Upper Bound on Kolmogorov Complexity by
	Hausdorff Dimension and Uniformly Optimal Prediction
1995-04	Birgitta König-Ries, Sven Helmer, Guido Moerkotte: An experimental
	study on the complexity of left-deep join ordering problems for cyclic
	queries
1995-05	Sophie Cluet, Guido Moerkotte: Efficient Evaluation of Aggregates on
	Bulk Types
1995-06	Sophie Cluet, Guido Moerkotte: Nested Queries in Object Bases
1995-07	Sophie Cluet, Guido Moerkotte: Query Optimization Techniques Ex-
	ploiting Class Hierarchies
1995-08	Markus Mohnen: Efficient Compile-Time Garbage Collection for Arbi-
	trary Data Structures
1995-09	Markus Mohnen: Functional Specification of Imperative Programs: An
	Alternative Point of View of Functional Languages
1995-10	Rainer Gallersdörfer, Matthias Nicola: Improving Performance in Repli-
	cated Databases through Relaxed Coherency
1995-11 *	M.Staudt, K.von Thadden: Subsumption Checking in Knowledge Bases
1995-12 *	G.V.Zemanek, H.W.Nissen, H.Hubert, M.Jarke: Requirements Analy-
	sis from Multiple Perspectives: Experiences with Conceptual Modeling
	Technology
1995-13 *	M.Staudt, M.Jarke: Incremental Maintenance of Externally Materialized
	Views
1995-14 *	P.Peters, P.Szczurko, M.Jeusfeld: Oriented Information Management:
	Conceptual Models at Work

1995-15 *	Matthias Jarke, Sudha Ram (Hrsg.): WITS 95 Proceedings of the 5th Annual Workshop on Information Technologies and Systems
1995-16 *	W.Hans, St.Winkler, F.Saenz: Distributed Execution in Functional Logic
	Programming
1996-01 *	Jahresbericht 1995
1996-02	Michael Hanus, Christian Prehofer: Higher-Order Narrowing with Defi- nitional Trees
1996-03 *	W.Scheufele, G.Moerkotte: Optimal Ordering of Selections and Joins in Acyclic Queries with Expensive Predicates
1996-04	Klaus Pohl: PRO-ART: Enabling Requirements Pre-Traceability
1996-05	Klaus Pohl: Requirements Engineering: An Overview
1996-06 *	M.Jarke, W.Marquardt: Design and Evaluation of Computer–Aided Process Modelling Tools
1996-07	Olaf Chitil: The Sigma-Semantics: A Comprehensive Semantics for Func- tional Programs
1996-08 *	S.Sripada: On Entropy and the Limitations of the Second Law of Ther- modynamics
1996-09	Michael Hanus (Ed.): Proceedings of the Poster Session of ALP96 - Fifth International Conference on Algebraic and Logic Programming
1996-09-0	Michael Hanus (Ed.): Proceedings of the Poster Session of ALP 96 - Fifth International Conference on Algebraic and Logic Programming: Introduction and table of contents
1996-09-1	Ilies Alouini: An Implementation of Conditional Concurrent Rewriting on Distributed Memory Machines
1996-09-2	Olivier Danvy, Karoline Malmkjær: On the Idempotence of the CPS Transformation
1996-09-3	Víctor M. Gulías, José L. Freire: Concurrent Programming in Haskell
1996-09-4	Sébastien Limet, Pierre Réty: On Decidability of Unifiability Modulo Rewrite Systems
1996-09-5	Alexandre Tessier: Declarative Debugging in Constraint Logic Program- ming
1996-10	Reidar Conradi, Bernhard Westfechtel: Version Models for Software Con- figuration Management
1996-11 *	C.Weise, D.Lenzkes: A Fast Decision Algorithm for Timed Refinement
1996-12 *	R.Dömges, K.Pohl, M.Jarke, B.Lohmann, W.Marquardt: PRO- ART/CE [*] — An Environment for Managing the Evolution of Chemical Process Simulation Models
1996-13 *	K.Pohl, R.Klamma, K.Weidenhaupt, R.Dömges, P.Haumer, M.Jarke: A Framework for Process-Integrated Tools
1996-14 *	R.Gallersdörfer, K.Klabunde, A.Stolz, M.Eßmajor: INDIA — Intelligent Networks as a Data Intensive Application, Final Project Report, June 1996
1996-15 *	H.Schimpe, M.Staudt: VAREX: An Environment for Validating and Re- fining Rule Bases
1996-16 *	M.Jarke, M.Gebhardt, S.Jacobs, H.Nissen: Conflict Analysis Across Heterogeneous Viewpoints: Formalization and Visualization
1996-17	Manfred A. Jeusfeld, Tung X. Bui: Decision Support Components on the Internet

1996-18	Manfred A. Jeusfeld, Mike Papazoglou: Information Brokering: Design, Search and Transformation
1996-19 *	P.Peters, M.Jarke: Simulating the impact of information flows in net-
1996-20	Worked organizations Matthias Jarke, Peter Peters, Manfred A. Jeusfeld: Model-driven plan-
1996-21 *	ning and design of cooperative information systems G.de Michelis, E.Dubois, M.Jarke, F.Matthes, J.Mylopoulos, K.Pohl, J.Schmidt, C.Woo, E.Yu: Cooperative information systems: a manifesto
1996-22 *	S.Jacobs, M.Gebhardt, S.Kethers, W.Rzasa: Filling HTML forms simul- taneously: CoWeb architecture and functionality
1996-23 *	M.Gebhardt, S.Jacobs: Conflict Management in Design
1997-01	Michael Hanus, Frank Zartmann (eds.): Jahresbericht 1996
1997-02	Johannes Faassen: Using full parallel Boltzmann Machines for Optimiza- tion
1997-03	Andreas Winter, Andy Schürr: Modules and Updatable Graph Views for PROgrammed Graph REwriting Systems
1997-04	Markus Mohnen, Stefan Tobies: Implementing Context Patterns in the Glasgow Haskell Compiler
1997-05 *	S.Gruner: Schemakorrespondenzaxiome unterstützen die paargramma- tische Spezifikation inkrementeller Integrationswerkzeuge
1997-06	Matthias Nicola, Matthias Jarke: Design and Evaluation of Wireless Health Care Information Systems in Developing Countries
1997-07	Petra Hofstedt: Taskparallele Skelette für irregulär strukturierte Prob- leme in deklarativen Sprachen
1997-08	Dorothea Blostein, Andy Schürr: Computing with Graphs and Graph Rewriting
1997-09	Carl-Arndt Krapp, Bernhard Westfechtel: Feedback Handling in Dy- namic Task Nets
1997-10	Matthias Nicola, Matthias Jarke: Integrating Replication and Commu- nication in Performance Models of Distributed Databases
1997-11 *	R. Klamma, P. Peters, M. Jarke: Workflow Support for Failure Manage- ment in Federated Organizations
1997-13	Markus Mohnen: Optimising the Memory Management of Higher-Order Functional Programs
1997-14	Roland Baumann: Client/Server Distribution in a Structure-Oriented Database Management System
1997-15	George Botorog: High-Level Parallel Programming and the Efficient Im- plementation of Numerical Algorithms
1998-01 *	Fachgruppe Informatik: Jahresbericht 1997
1998-02	Stefan Gruner, Manfred Nagel, Andy Schürr: Fine-grained and
	Structure-Oriented Document Integration Tools are Needed for Devel- opment Processes
1998-03	Stefan Gruner: Einige Anmerkungen zur graphgrammatischen Spezifika- tion von Integrationswerkzeugen nach Westfechtel, Janning, Lefering und Schürr
1998-04 *	O. Kubitz: Mobile Robots in Dynamic Environments
1998-05	Martin Leucker, Stephan Tobies: Truth - A Verification Platform for Distributed Systems

1998-06 *	Matchias Oliver Berger: DECT in the Factory of the Future
1998-07	M. Arnold, M. Erdmann, M. Glinz, P. Haumer, R. Knoll, B. Paech, K.
	Pohl, J. Ryser, R. Studer, K. Weidenhaupt: Survey on the Scenario Use
	in Twelve Selected Industrial Projects
1998-09 *	Th. Lehmann: Geometrische Ausrichtung medizinischer Bilder am
	Beispiel intraoraler Radiographien
1998-10 *	M. Nicola, M. Jarke: Performance Modeling of Distributed and Repli-
	cated Databases
1998-11 *	Ansgar Schleicher, Bernhard Westfechtel, Dirk Jäger: Modeling Dynamic
	Software Processes in UML
1998-12 *	W. Appelt, M. Jarke: Interoperable Tools for Cooperation Support using
	the World Wide Web
1998-13	Klaus Indermark: Semantik rekursiver Funktionsdefinitionen mit Strik-
	theits information
1999-01 *	Jahresbericht 1998
1999-02 *	F. Huch: Verifcation of Erlang Programs using Abstract Interpretation
	and Model Checking — Extended Version
1999-03 *	R. Gallersdörfer, M. Jarke, M. Nicola: The ADR Replication Manager
1999-04	María Alpuente, Michael Hanus, Salvador Lucas, Germán Vidal: Spe-
	cialization of Functional Logic Programs Based on Needed Narrowing
1999-05 *	W. Thomas (Ed.): DLT 99 - Developments in Language Theory Fourth
	International Conference
1999-06 *	Kai Jakobs, Klaus-Dieter Kleefeld: Informationssysteme für die ange-
	wandte historische Geographie
1999-07	Thomas Wilke: CTL+ is exponentially more succinct than CTL
1999-08	Oliver Matz: Dot-Depth and Monadic Quantifier Alternation over Pic-
	tures
2000-01 *	Jahresbericht 1999
2000-02	Jens Vöge, Marcin Jurdzinski A Discrete Strategy Improvement Algo-
	rithm for Solving Parity Games
2000-03	D. Jäger, A. Schleicher, B. Westfechtel: UPGRADE: A Framework for
2000.04	Building Graph-Based Software Engineering Tools
2000-04	Andreas Becks, Stefan Sklorz, Matthias Jarke: Exploring the Semantic
	Structure of Technical Document Collections: A Cooperative Systems
2000 05	Approach Marsila Cale and Camerating Decomposit Management
2000-05	Mareike Schoop: Cooperative Document Management
2000-00	tional Workshop on the Language Action Dereparties on Communication
	Modelling
2000.07 *	Markus Mohnon Piotor Koopman (Eds.): Proceedings of the 19th Inter-
2000-01	national Workshop of Functional Languages
2000-08	Thomas Arts Thomas Noll: Verifying Generic Erlang Client-Server Im-
2000 00	plementations
2001-01 *	Jahresbericht 2000
2001-02	Benedikt Bollig, Martin Leucker: Deciding LTL over Mazurkiewicz
-	Traces
2001-03	Thierry Cachat: The power of one-letter rational languages

2001-04	Benedikt Bollig, Martin Leucker, Michael Weber: Local Parallel Model Checking for the Alternation Free my Calculus
2001.05	Banadilet Ballig Martin Laudren Thomas Nell: Basular MSC Languages
2001-05	Achim Diumongath, Drafu Decemicable Change and Manadia Second
2001-00	Order Logic
2001-07	Martin Grohe, Stefan Wöhrle: An Existential Locality Theorem
2001-08	Mareike Schoop, James Taylor (eds.): Proceedings of the Sixth Interna- tional Workshop on the Language-Action Perspective on Communication Modelling
2001-09	Thomas Arts, Jürgen Giesl: A collection of examples for termination of term rewriting using dependency pairs
2001-10	Achim Blumensath: Axiomatising Tree-interpretable Structures
2001-11	Klaus Indermark Thomas Noll (eds.): Kolloquium Programmier-
2001-11	sprachen und Grundlagen der Programmierung
2002-01 *	Jahresbericht 2001
2002-02	Jürgen Giesl, Aart Middeldorp: Transformation Techniques for Context- Sensitive Rewrite Systems
2002-03	Benedikt Bollig, Martin Leucker, Thomas Noll: Generalised Regular
	MSC Languages
2002-04	Jürgen Giesl, Aart Middeldorp: Innermost Termination of Context-
	Sensitive Rewriting
2002-05	Horst Lichter, Thomas von der Maßen, Thomas Weiler: Modelling Re-
2002 00	quirements and Architectures for Software Product Lines
2002-06	Henry N Adorna: 3-Party Message Complexity is Better than 2-Party
2002-00	Ones for Proving Lower Bounds on the Size of Minimal Nondeterministic Finite Automata
2002-07	Jörg Dahman: Invariant Image Object Recognition using Caussian Mix-
2002-07	ture Densities
2002-08	Markus Mohnen: An Open Framework for Data-Flow Analysis in Java
2002-09	Markus Mohnen: Interfaces with Default Implementations in Java
2002-10	Martin Leucker: Logics for Mazurkiewicz traces
2002-11	Jürgen Giesl, Hans Zantema: Liveness in Rewriting
2003-01 *	Jahresbericht 2002
2003-02	Jürgen Giesl, René Thiemann: Size-Change Termination for Term Rewriting
2003-03	Jürgen Giesl, Deepak Kapur: Deciding Inductive Validity of Equations
2003-04	Jürgen Giesl, René Thiemann, Peter Schneider-Kamp, Stephan Falke:
	Improving Dependency Pairs
2003-05	Christof Löding, Philipp Rohde: Solving the Sabotage Game is PSPACE- hard
2003-06	Franz Josef Och: Statistical Machine Translation: From Single-Word
	Models to Alignment Templates
2003-07	Horst Lichter, Thomas von der Maßen, Alexander Nyßen, Thomas
	Weiler: Vergleich von Ansätzen zur Feature Modellierung bei der Soft- wareproduktlinienentwicklung
2003-08	Jürgen Giesl, René Thiemann, Peter Schneider-Kamp, Stephan Falke
	Mechanizing Dependency Pairs
2004-01 *	Fachgruppe Informatik: Jahresbericht 2003

2004-02	Benedikt Bollig, Martin Leucker: Message-Passing Automata are expres-
2004 02	sively equivalent to EMSO logic
2004-03	International Workshop on Higher Order Reputiting
2004-04	Slim Abdennedher, Christophe Bingeissen (eds.): BULE 04 – Fifth In-
2004-04	tornational Workshop on Bula Based Programming
2004-05	Herbert Kuchen (ed.): WFLP $04 - 13$ th International Workshop on Func-
2001 00	tional and (Constraint) Logic Programming
2004-06	Sergio Antov. Yoshihito Toyama (eds.): WRS 04 – 4th International
	Workshop on Reduction Strategies in Rewriting and Programming
2004-07	Michael Codish, Aart Middeldorp (eds.): WST 04 – 7th International
	Workshop on Termination
2004-08	Klaus Indermark, Thomas Noll: Algebraic Correctness Proofs for Com-
	piling Recursive Function Definitions with Strictness Information
2004-09	Joachim Kneis, Daniel Mölle, Stefan Richter, Peter Rossmanith: Param-
	eterized Power Domination Complexity
2004-10	Zinaida Benenson, Felix C. Gärtner, Dogan Kesdogan: Secure Multi-
	Party Computation with Security Modules
2005-01 *	Fachgruppe Informatik: Jahresbericht 2004
2005-02	Maximillian Dornseif, Felix C. Gärtner, Thorsten Holz, Martin Mink: An
	Offensive Approach to Teaching Information Security: "Aachen Summer
2005 02	School Applied IT Security"
2005-03	Jurgen Giesl, Rene Thiemann, Peter Schneider-Kamp: Proving and Dis-
2005 04	proving Termination of Higher-Order Functions
2003-04	the Steiner Tree Problem
2005-05	Fahien Pouget Thorsten Holz: A Pointillist Approach for Comparing
2000 00	Honevpots
2005-06	Simon Fischer, Berthold Vöcking: Adaptive Routing with Stale Informa-
	tion
2005-07	Felix C. Freiling, Thorsten Holz, Georg Wicherski: Botnet Tracking: Ex-
	ploring a Root-Cause Methodology to Prevent Distributed Denial-of-
	Service Attacks
2005-08	Joachim Kneis, Peter Rossmanith: A New Satisfiability Algorithm With
	Applications To Max-Cut
2005-09	Klaus Kursawe, Felix C. Freiling: Byzantine Fault Tolerance on General
	Hybrid Adversary Structures
2005-10	Benedikt Bollig: Automata and Logics for Message Sequence Charts
2005-11	Simon Fischer, Berthold Vöcking: A Counterexample to the Fully Mixed
2005 12	Nash Equilibrium Conjecture
2005-12	Neeraj Mittal, Felix Freiling, S. Venkatesan, Lucia Draque Penso: Ef-
	incient Reductions for Wait-Free Termination Detection in Faulty Dis-
2005-13	Carola Dalporta Callet Hugues Fauconniar Folix C. Frailing: Powisiting
2000-10	Failure Detection and Consensus in Omission Failure Environments
2005-14	Felix C. Freiling, Sukumar Ghosh: Code Stabilization
2005-15	Uwe Naumann: The Complexity of Derivative Computation

2005-16	Uwe Naumann: Syntax-Directed Derivative Code (Part I: Tangent- Linear Code)
2005-17	Uwe Naumann: Syntax-directed Derivative Code (Part II: Intraprocedu- ral Adioint Code)
2005-18	Thomas von der Maßen, Klaus Müller, John MacGregor, Eva Geis- berger, Jörg Dörr, Frank Houdek, Harbhajan Singh, Holger Wußmann, Hans-Veit Bacher, Barbara Paech: Einsatz von Features im Software- Entwicklungsprozess - Abschlußbericht des GI-Arbeitskreises "Features"
2005-19	Uwe Naumann, Andre Vehreschild: Tangent-Linear Code by Augmented LL-Parsers
2005-20	 Felix C. Freiling, Martin Mink: Bericht über den Workshop zur Ausbildung im Bereich IT-Sicherheit Hochschulausbildung, berufliche Weiterbildung, Zertifizierung von Ausbildungsangeboten am 11. und 12. August 2005 in Köln organisiert von RWTH Aachen in Kooperation mit BITKOM, BSI, DLR und Gesellschaft fuer Informatik (GI) e.V.
2005-21	Thomas Noll, Stefan Rieger: Optimization of Straight-Line Code Revis- ited
2005-22	Felix Freiling, Maurice Herlihy, Lucia Draque Penso: Optimal Random- ized Fair Exchange with Secret Shared Coins
2005-23	Heiner Ackermann, Alantha Newman, Heiko Röglin, Berthold Vöcking: Decision Making Based on Approximate and Smoothed Pareto Curves
2005-24	Alexander Becher, Zinaida Benenson, Maximillian Dornseif: Tampering with Motes: Real-World Physical Attacks on Wireless Sensor Networks
2006-03	Uwe Naumann: Intraprocedural Adjoint Code Generated by the Differentiation-Enabled NAGWare Fortran Compiler
2006-04	Ebadollah Varnik, Uwe Naumann, Andrew Lyons: Toward Low Static Memory Jacobian Accumulation
2006-06	Joachim Kneis, Daniel Mölle, Stefan Richter, Peter Rossmanith: Divide- and-Color
2006-07	Thomas Colcombet, Christof Löding:: Transforming structures by set interpretations
2006-08	Uwe Naumann, Yuxiao Hu: Optimal Vertex Elimination in Single- Expression-Use Graphs
2006-10	Mesut Günes, Alexander Zimmermann, Martin Wenig, Jan Ritzerfeld, Ulrich Meis: From Simulations to Testbeds - Architecture of the Hybrid MCG-Mesh Testbed
2006-11	Bastian Schlich, Michael Rohrbach, Michael Weber, Stefan Kowalewski: Model Checking Software for Microcontrollers

 * These reports are only available as a printed version.

 $Please \ {\tt contact \ biblio@informatik.rwth-aachen.de \ to \ obtain \ copies.}$