Practical Proof Methods for Combined Modal and Temporal Logics

Ullrich Hustadt

Centre for Agent Research and Development, Manchester Metropolitan University,
Chester Street, Manchester M1 5GD, United Kingdom
U.Hustadt@doc.mmu.ac.uk

For a number of years, temporal and modal logics have been applied outside pure logic in areas such as formal methods, theoretical computer science and artificial intelligence. In our research we are particularly interested in the use of modal logics in the characterisation of complex components within software systems as *intelligent* or *rational* agents. This approach allows the system designer to analyse applications at a much higher level of abstraction. In order to reason about such agents, a number of theories of rational agency have been developed, for example the BDI (Rao and Georgeff 1991) and KARO (van Linder, van der Hoek, and Meyer 1996) frameworks. The leading agent theories and formal methods in this area all share similar logical properties, more precisely, they all exhibit (i) an *informational* component, being able to represent an agent's beliefs (by the modal logic KD45) or knowledge (by the modal logic S5), (ii) a *dynamic* component, allowing the representation of dynamic activity (by temporal or dynamic logic), and, (iii) a *motivational* component, often representing the agents desires, intentions or goals (by the modal logic KD).

While many of the basic properties of such combinations of modal and temporal or dynamic logics are well understood (Baader and Ohlbach 1995; Fagin et al. 1996; Gabbay 1996; Wolter 1998), very little work has been carried out on practical proof methods for such logics.

Our aim in recent work has been to develop proof methods that are general enough to capture a wide range of combinations of temporal and modal logics, but still provide viable means for effective theorem proving. Currently, we are investigating an approach with the following properties:

- The approach covers the combination of discrete, linear, temporal logic with extensions of multi-modal K_m by any combination of the axiom schemata 4, 5, B, D, and T. This extends the results presented in (Dixon, Fisher and Wooldridge 1998; Wooldridge, Dixon, and Fisher 1998).
- Instead of combining two calculi operating according to the same underlying principles, like for example two tableaux-based calculi, we combine two different approaches to theorem-proving in modal and temporal logics, namely the translation approach for modal logics (using first-order resolution) and the SNF approach for temporal logics (using modal resolution).
- The particular translation we use has only recently been proposed by de Nivelle (1999) and can be seen as a special case of the T-encoding introduced by Ohlbach (1998). It allows for conceptually simple decision procedures for

extensions of K4 by ordered resolution without any reliance on loop checking or similar techniques.

In more detail, this approach consists of (i) a normal form transformation of formulae of the combined logics into sets of so-called *SNF_K clauses* (similar to those presented in Dixon et. al. 1998), (ii) a translation of modal subformula in SNF_K clauses into a first-order language, and (iii) a calculus $\mathsf{C}_{\mathsf{MTL}}$ for the combined logic which can be divided into standard resolution inference rules for first-order logic and a modified version of the temporal resolution inference rules of Fisher (1991).

The calculus $\mathsf{C}_{\mathsf{MTL}}$ provides a decision procedure for combinations of the basic multi-modal logic K_m and its extensions by arbitrary combinations of the axiom schemata 4, 5, B, D, and T with linear, temporal logic.

For a more detailed description of our approach see Hustadt, Dixon, Schmidt, and Fisher (2000). Related work on proof methods for the KARO framework of agency can be found in Hustadt, Dixon, Schmidt, Fisher, Meyer, and van der Hoek (2000).

References

Baader, F. and Ohlbach, H. J. (1995). A multi-dimensional terminological knowledge representation language. *Journal of Applied Non-Classical Logics*, 2:153–197.

Blackburn, P. and de Rijke, M. (1997). Why combine logics? *Studia Logica*, 59(1):5–27.

de Nivelle, H. (1999). Translation of S4 into GF and 2VAR. Manuscript.

Dixon, C., Fisher, M., and Wooldridge, M. (1998). Resolution for temporal logics of knowledge. *Journal of Logic and Computaton*, 8(3):345–372.

Fagin, R., Halpern, J. Y., Moses, Y., and Vardi, M. Y. (1996). *Reasoning About Knowledge*. MIT Press.

Fisher, M. (1991). A Resolution Method for Temporal Logic. In *Proc. IJCAI'91*, pages 99–104. Morgan Kaufmann.

Gabbay, D. M. (1996). Fibred semantics and the weaving of logics. Part 1. Modal and intuitionistic logics. *Journal of Symbolic Logic*, 61(4):1057–1120.

Hustadt, U., Dixon, C., Schmidt, R. A., and Fisher, M. (2000). Normal Forms and Proofs in Combined Modal and Temporal Logics. In *Proc. FroCoS'2000*, *LNAI* 1794, pages 73–87. Springer.

Hustadt, U., Dixon, C., Schmidt, R. A., Fisher, M., Meyer, J-J., and van der Hoek, W. (2000) Verification within the KARO Agent Theory. In Proc. First Goddard Workshop on Formal Approaches to Agent-Based Systems. Springer, to appear.

Ohlbach, H. J. (1998). Combining Hilbert style and semantic reasoning in a resolution framework. In *Proc. CADE-15*, *LNAI* 1421, pages 205–219. Springer.

Rao, A. S. and Georgeff, M. P. (1991). Modeling agents withing a BDI-architecture. In *Proc. KR-91*, pages 473–484. Morgan Kaufmann.

van Linder, B., van der Hoek, W. and Ch. Meyer, J.-J. (1996). How to motivate your agents. In *Intelligent Agents II*, pages 17–32, *LNAI* 1037. Springer.

Wolter, F. (1998). Fusions of Modal Logics revisited, *Advances in Modal Logic*, Volume 1, *CSLI Lecture Notes* 87, pages 361–379. CSLI Publications.

Wooldridge, M., Dixon, C., and Fisher, M. (1998). A tableau-based proof method for temporal logics of knowledge and belief. *Journal of Applied Non-Classical Logics*, 8(3):225–258.